

C/Front Reference Guide

C/FRONT REFERENCE GUIDE

Information in this document, including URL and other Internet Web site references, is subject to change without notice. Unless otherwise noted, the companies, organizations, products, domain names, e-mail addresses, logos, people, places, and events depicted in examples herein are fictitious. No association with any real company, organization, product, domain name, e-mail address, logo, person, place, or event is intended or should be inferred. Complying with all applicable copyright laws is the responsibility of the user. Without limiting the rights under copyright, no part of this document may be reproduced, stored in or introduced into a retrieval system, or transmitted in any form or by any means (electronic, mechanical, photocopying, recording, or otherwise), or for any purpose, without the express written permission of Microsoft Corporation.

Microsoft may have patents, patent applications, trademarks, copyrights, or other intellectual property rights covering subject matter in this document. Except as expressly provided in any written license agreement from Microsoft, the furnishing of this document does not give you any license to these patents, trademarks, copyrights, or other intellectual property.

© 2007 Microsoft Corporation. All rights reserved.

Microsoft, MS-DOS, Windows, Windows Server, Windows Vista, Application Server for Microsoft Dynamics NAV, AssistButton, C/AL, C/Front, C/Side, FlowField, FlowFilter, C/Side Database Server for Microsoft Dynamics NAV, Microsoft Business Solutions–Navision, Microsoft Dynamics NAV, Microsoft Dynamics NAV Debugger, Navision, NAV ODBC, SIFT, SIFTWARE, SQL Server, SumIndex, SumIndexField are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

All other trademarks are property of their respective owners.

PREFACE

This book is a manual for the C/Front application programming interface that can be used to access a C/SIDE[®] database. This manual describes how to install and use C/Front. This book is part of a comprehensive set of documentation and Help materials for Microsoft Dynamics[™] NAV.

You should also be familiar with the symbols and typographical conventions used in the Microsoft Dynamics NAV manuals. In the list below, you can see how various elements of the program are distinguished by special typefaces and symbols:

Appearance	Element
Ctrl	Keys on the keyboard. They are written in small capitals.
<u>D</u> esign	Menu items and buttons in windows. They always start with a capital letter, and the access key is underlined.
Address	Field names. They appear in medium bold and start with a capital letter.
Department	Names of windows, boxes and tabs. They appear in medium bold italics and start with a capital letter.
Hansen	Text that you must enter, for example: "...enter Yes in this field." It is written in italics.
fin.flf	File names. They are written with the Courier font and lowercase letters.
↑ ↓ ▼ *▶ ...	The special symbols that can be seen in the windows on the screen.

TABLE OF CONTENTS

Chapter 1	Introduction to C/Front	1
	Introduction to C/Front	2
	Service Packs and Security Updates	5
Chapter 2	Review of Standard Operations	7
	The Standard Operations	8
Chapter 3	A Sample Application	21
	Building and Running the Sample Application	22
Chapter 4	The Library Functions	25
	Library Functions Grouped by Use	26
	Library Functions in Alphabetical Order	33
Appendix A	C/Front Library Specifications	143
	C/Front Library Specifications	144
Appendix B	The Alpha Type	147
	Alpha Type	148

Chapter 1

Introduction to C/Front

This is an introduction to C/Front and describes the contents of C/Front, the system requirements, standby/hibernation and multilanguage.

This chapter contains:

- Introduction to C/Front
- Service Packs and Security Updates

1.1 Introduction to C/Front

C/Front is an application programming interface that can be used to access a C/SIDE® database. C/Front facilitates high-level interaction with the C/SIDE database manager, and allows C developers to manipulate any C/SIDE database. C/Front has been primarily designed to allow developers to retrieve and update tables and not for executing business logic.

The central component of C/Front is a library of C functions. These functions give you access to every aspect of data storage and maintenance, and allow you to integrate both standard and custom applications with your C/SIDE database.

This Manual

This manual explains how to use the library functions to access the features and facilities of a C/SIDE database. It consists of five chapters:

- **Chapter 1 – Introduction to C/Front:**
Lists the contents of C/Front and explains how to configure C/Front.
- **Chapter 2 – Review of Standard Operations:**
Explains and demonstrates how to use some of the library functions in frequent operations.
- **Chapter 3 – A Sample Application:**
Explains how to run the sample application that comes with C/Front. The source code is available on the Microsoft Dynamics™ NAV product DVD in the file called `sample.c`.
- **Chapter 4 – The Library Functions:**
All of the C/Front functions are listed and described.
Appendix A lists the type and constant definitions.
Appendix B describes nonstandard data formats.

It is assumed that the reader has a good knowledge of C and C/SIDE. For further information about these subjects, refer to your C manuals and the *Application Designer's Guide*.

The Contents of C/Front

C/Front provides an interface to the C language, and is distributed on the Dynamics NAV product DVD. The following files are distributed:

File name	Used for
<code>cfront.dll</code>	C/Front C-API library
<code>cfrontsql.dll</code>	C/Front C-API library
<code>cf.h</code>	C/Front header file
<code>libload.c</code>	Source file containing functions to load and unload <code>cfront.dll</code>
<code>dberror.txt</code>	Database error/return codes

File name	Used for
<code>cfront.ocx</code>	C/Front OCX

In addition to these files, C/Front contains a sample application – see Building and Running the Sample Application on page 22 for details.

Before you can use C/Front, you must copy the following files from Dynamics NAV to the directory where you have installed C/Front:

```
dbm.dll
nc_netb.dll
nc_tcp.dll
slave.exe
fin.etx
fin.stx
fin.flf
```

You must also have a database. These files are all part of a standard Dynamics NAV installation. Last minute changes to C/Front are documented in the file `Readme.txt` that is distributed on the Dynamics NAV product DVD. Please read this file before beginning the installation.

Installation

The `Readme.txt` file on the product DVD contains detailed and up-to-date information on installing C/Front.

System Requirements

C/Front can be used on Windows XP and Windows Vista. It has been tested with the Watcom C compiler, version 10.5a and with Microsoft Visual C++, version 5.00. It can also be used with any other compiler that can load and use DLLs correctly, but note that the functions in the C/Front DLL module are called with the `_cdecl` calling convention.

Standby and Hibernation

C/Front supports the standby and hibernation facilities provided by Windows.

Putting your computer on standby means that the entire computer switches to a low power state. When on standby all devices, such as the monitor and hard disks, turn off and your computer uses less power. When you want to use the computer again, it comes out of standby quickly, and your desktop is restored exactly as you left it. Standby is particularly useful for conserving battery power in portable computers. Because standby does not save your desktop state to disk, a power failure while on standby can cause unsaved information to be lost.

Putting your computer in hibernation means that before shutting down your computer saves everything that is currently in memory to disk, turns off your monitor and hard disk, and then turns off your computer. When you reactivate your computer, your desktop is restored exactly as you left it. It takes longer to bring your computer out of hibernation than out of standby.

- Shutting Down** The individual workstations can specify that their computer should go to standby or hibernate after being idle for a certain length of time. It is also possible to make the computer go to standby from the Shut Down dialog box in Windows.
- Windows will not go to standby or hibernation if there is an open server connection from C/Front.
- If you attempt to make the computer go to standby from the Windows Shut Down dialog box, a window will appear informing you that C/Front is busy and that shutting down is not yet possible.
- If you click Cancel in this window, the hibernation or standby procedure will be postponed. Alternatively, you can ignore this window and the computer will shut down when C/Front has completed its task.
- Restarting** When you restart your computer after it has gone to standby or is in hibernation it will restart with the desktop exactly as it was when you left it. However, the information displayed will also be the same and will therefore not necessarily be up to date.
- The window will not be updated until you use the program and actively update the window in question.

Multilanguage

Dynamics NAV is multilanguage enabled, allowing users to change application language on the fly. This is achieved by adding captions to the objects in the database. These captions contain the names of the database objects in the languages that are available in your application. However, C/Front does not have any table or field caption functions that you can use to identify these different names.

Any programs that use C/Front will therefore not be able to identify the names of the database objects in the various application languages that are available. To obtain this information you can generate a text file listing all of the objects in the database and the captions that they contain.

To generate this text file:

- 1 Open the Object Designer and select all the objects.
- 2 Click Tools, Translate, Export.

This file will list all the objects in the database and each object will be listed once for each language that it used in your application.

Here is an example:

T3-F2-P8629-A1033-L999:Due Date Calculation

Table 3, Field 2, Property 8629(Caption), Language ID 1033 (US English), Max. Length 999, the name of the object.

You can now use the information contained in this text file in the program that uses C/Front.

1.2 Service Packs and Security Updates

The installation is not complete until you have installed the latest service packs and applied the latest security updates to your system. Keeping your system up-to-date by installing the latest service packs is one of most important things you can do in managing the security of your system.

You should visit Microsoft Update and install all the relevant updates on every computer in your Dynamics NAV installation. We also recommend that you enable Automatic Updates on each computer so that they can receive security & critical updates automatically.

Chapter 2

Review of Standard Operations

C/Front contains functions that allow you to perform all the standard operations that are used to maintain a C/SIDE database.

The chapter contains the following topics:

- The Standard Operations

2.1 The Standard Operations

Maintaining a C/SIDE database involves a number of operations:

- Determining which DLL to Use
- Initializing the Library
- Connecting to a Server and Opening a Database
- Opening a Company
- Opening a Table
- Using Filters
- Using Keys
- Finding a Record
- Inserting a Record
- Modifying a Record
- Deleting a Record
- Editing a Field in a Record
- Handling Errors and Exceptions

These operations are illustrated with the help of small sample routines. All of the functions are fully explained in chapter 5, "The Library Functions".

Determining which DLL to Use

Dynamic NAV can run on two different servers and C/Front therefore comes with two different DLLs: `CFront.DLL` and `CFrontSQL.DLL`. They will both be installed when you install C/Front.

If you are running on C/SIDE Database Server you must use `CFront.DLL`. If you are running on Microsoft SQL Server you must use `CFrontSQL.DLL`.

Initializing the Library

To initialize the library and configure the environment, call `DBL_Init`. This function initializes internal data structures, creates buffers, and loads the dynamic link libraries required by the library.

As shown below, this operation is usually performed in the `main()` function of the C program:

```
void main(int argc, char* argv[])

{
    DBL_Init();
    /* ... */
    DBL_Exit();
    exit(0);
}
```


Connecting to a Server and Opening a Database

C/Front contains a single function that you can use to connect with a server and open a database. This function works with both C/SIDE Database Server and the Microsoft SQL Server Option and enables you to connect to a server, open a database and specify the kind of authentication to use.

Microsoft SQL Server Option

The following example illustrates how to use this function with the SQL Server Option.

```
#define DRIVERVERNAME "NDBCS"
#define SERVERNAME "SQL 1"
#define NETTYPE      "Named Pipes"
#define DATABASENAME "My Database.mdf"
#define CACHESIZE    0
#define USECOMMITCACHE 0
#define USENTAUTHENTICATION 1
#define USERID      ""
#define PASSWORD    ""

DBL_ConnectServerandOpenDatabase(DRIVERNAME, SERVERNAME, NETTYPE,
DATABASENAME, CACHESIZE, USECOMMITCACHE, USENTAUTHENTICATION, USERID,
PASSWORD);
/* ... access the database ... */

DBL_DisconnectServer();

/* ... */
```

If you are using SQL Server you still have to enter a zero value for CacheSize or UseCommitCache even though they only apply to the C/SIDE Database Server.

If you select Windows Authentication (UseNTAuthentication=1) then you do not have to supply a user ID or a password. However you must enter two empty sets of quotes ("") in order to comply with the syntax.

You must run this function again if you want to open another database. This database can be on the same server or on another server.

C/SIDE Database Server

The library can either run in 'local mode' or be connected to a remote server in a network. When the user connects to a C/SIDE Database Server in a network a database is opened automatically by the server. When the library is run in 'local mode' (the database is stored on the same computer as your application), a database must be opened explicitly.

The following routine works in both environments:

```
#define DRIVERVERNAME "NDBCN"
#define SERVERNAME "accounting"
#define NETTYPE      "tcp"
#define DATABASENAME "Database.fdb"
#define CACHESIZE    1000
#define USECOMMITCACHE 0

DBL_BOOL RemoteMode = 0;
```

```

/* ... */

if (RemoteMode)
DBL_ConnectServerandOpenDatabase(DRIVERNAME, SERVERNAME, NETTYPE,
DATABASENAME, CACHESIZE, USECOMMITCACHE);

/* ... access the database ... */

if (RemoteMode)
  DBL_DisconnectServer();
else
  DBL_CloseDatabase();

/* ... */

```

If the open/connect operation fails, the function raises an exception that terminates the application.

Only one database/server connection can be open at a time.

For more information about exceptions, see Handling Errors and Exceptions on page 17.

Note

.....
C/FRONT does not support the use of extended characters in directory and database names.
.....

Opening a Company

A database consists of one or more companies. A company is a "subdatabase," whose primary use is to separate and group data within one database. A company "bundles" one or more tables together into a logical structure that is identified by the company name. The tables within a company do not need not have anything in common other than the shared company name.

Only one company can be open at a time. You must open a company before the application can access the data in the database tables. By opening a company, you specify which data tables can be opened by DBL_OpenTable.

```

#define COMPANYNAME "Test Company"
DBL_OpenCompany(COMPANYNAME);
/* ... open tables ... */
DBL_CloseCompany();

```

If the company that you want to open does not exist, the function raises an exception that terminates the application.

For more information about exceptions, see Handling Errors and Exceptions on page 17.

A database maintains a list of the companies that it contains. To retrieve the names of all the companies contained in a database, execute the DBL_NextCompany function in a loop:

```
DBL_U8 *CompName;
```

```

for (CompName = NULL; CompName = DBL_NextCompany(CompName);)
{
/* ... */
}

```

For more information about companies, see the *Application Designer's Guide*.

Opening a Table

A database contains a number of tables that can be manipulated with the functions in the library. You can have any number of tables, within a single company, open at the same time. A table is identified by a unique number. When a table is opened, the database manager returns a unique handle, which remains valid until the table is closed. This handle must be passed to all operations that are carried out on the table.

If you do not know the number of the table that you want to open, you can look it up with the library function `DBL_TableNo`. This function requires the name of the table as a parameter. Table names are also unique.

Manipulating a table often requires the use of filters and keys. Filters and keys are bound to a handle and not to a table. This allows you to open various "views" of a single table, each with its own key and set of filters, to suit the needs of individual applications.

The following example illustrates how a table is represented by its handle, with the symbolic name `hTable`.

```

#define TABLENAME "MyTable"

DBL_HTABLE hTable;
DBL_S32 TableNo;

TableNo = DBL_TableNo(TABLENAME);

if (TableNo != 0)
{
DBL_OpenTable(&hTable, TableNo);
/* ... access data in the table ... */
DBL_CloseTable(hTable);
}

```

Filters and keys are discussed in the next section. For more information about tables, see the *Application Designer's Guide*.

Using Filters

Filters limit the number of records that are being manipulated. Filters limit the number of records that are selected for calculating column sums, in record searches, and in other activities. The library contains two functions that can set a filter: `DBL_SetFilter` and `DBL_SetRange`. `DBL_SetRange` is a subfunction of `DBL_SetFilter`.

In the following example, the operations will only affect records with Field Number 2 that are within the ranges 100..200 and 300..400.

```

#define TABLENUMBER 15

```

```

DBL_HTABLE hTable;
DBL_S32    FieldNo;
/* ... */
DBL_OpenTable(&hTable, TABLENUMBER);
FieldNo = 2;
DBL_SetFilter(hTable, FieldNo, "100..200&300..400", NULL);
/* ... retrieve data within the specified range ... */
DBL_CloseTable(hTable);
/* ... */

```

Setting a Range

The DBL_SetRange function is used in the following way:

```

DBL_HTABLE hTable;
DBL_S32    FieldNo = 2;
DBL_S32    MinValue = 100;
DBL_S32    MaxValue = 200;

/* ... */
DBL_SetRange(hTable, FieldNo, &MinValue, &MaxValue);
/* ... retrieve data within the specified range ... */
/* ... */

```

DBL_SetFilter can use the & or | operators to specify a complex interval as the condition for a field, but DBL_SetRange can specify only a single interval. A filter can be retrieved by the function DBL_GetFilter, and the range by DBL_GetRange.

For more information about filters, see the *Application Designer's Guide*.

Using Keys

You can use keys to sort the records in a table according to the values in specified fields, for example, in ascending order. You can find a field that contains a specific value much faster when the records are sorted (using a key). A key maintains the relationship between the records, in a structure called an index.

A key is composed of one or more fields. You specify how these fields are ordered in C/SIDE. Keys cannot be defined or modified in C/FRONT.

A table can contain up to 20 keys, each with its own index. The first key in a table is the primary key and the data it contains must always be unique. The index for each key is maintained by the C/SIDE database manager.

All of the other keys are secondary keys. Multiple secondary keys may be active simultaneously. The secondary keys do not have to contain unique data. Records containing identical data in secondary key fields are "sub-sorted" once again, according to the value of the primary key because the primary key is always in effect with the current secondary key.

Keys can be active or inactive. Keys can be activated or deactivated in C/SIDE, not in C/FRONT. Only active keys are available to library functions.

When you insert, delete or modify a record, the indexes that are maintained by all of the active keys are automatically updated to reflect any changes that are made to the table. The indexes of inactive keys are not updated. If at some point you reactivate a key (in C/SIDE) that has been inactive, you must allow some time for the application to

rebuild the index structure. This may require some additional disk space if the space that has been allocated to the database is nearly full, because each key occupies space in the database.

The Current Key

Although keys can only be defined in C/SIDE, the key needed for the current application can be selected in the library. This key is then called the current key. The current key is always attached to the table handle, not to the table itself.

The following example shows how to select the current key:

```
DBL_HTABLE hTable;
DBL_S32    Key[DBL_MaxFieldsPerKey+1];

/* ... */

Key[0] = 3;
Key[1] = 0; /* Zero-terminated list */
DBL_SetCurrentKey(hTable, Key);

/* ... scan table sorted by field number 3 ... */

/* ... */
```

The primary key is selected when you call `DBL_SetCurrentKey` with the `Key` parameter equal to `NULL`.

Each table maintains a list of all its keys. To retrieve this list, execute the `DBL_NextKey` function in a loop:

```
DBL_HTABLE hTable;
DBL_S32    *Key;
DBL_S32    *Field;

/* ... */

for (Key = NULL; Key = DBL_NextKey(hTable, Key); )
{
    printf("Key contains the following field number(s):\n");

    for (Field = Key; *Field; Field++)
        printf("%d\n", *Field);
}

/* ... */
```

Other key functions are:

Function	Purpose
<code>DBL_GetCurrentKey</code>	Retrieves the key that is currently selected.
<code>DBL_KeySumFields</code>	Returns a list of <code>SumIndexField</code> [®] numbers for a specified key.

For more information about keys and `SumIndexFields`, see the *Application Designer's Guide*.

Finding a Record

Two functions are used to retrieve records:

Function	Purpose
DBL_FindRec	Locates a record that contains given values in the fields of the current key, and copies it to a buffer. The current filters are used when searching.
DBL_NextRec	Uses the current sorting sequence to retrieve a record in the table relative to a specified record, and copies it to a buffer. The current filters are used when searching.

To create a record buffer, call `DBL_AllocRec`. This function allocates an area of memory equal to the size of the record, including virtual fields (`FlowField®` and `FlowFilter®`). You must remove the record buffer when you are finished using it, by calling `DBL_FreeRec`.

In the following routine, `DBL_FindRec` searches for the first record in the table, copies it to a buffer and performs some operations on it. Control is then passed to `DBL_NextRec`, which steps through the entire file performing the same operations on each record.

```
DBL_HTABLE hTable;
DBL_HREC   hRec;

/* ... */

/* Allocate memory for the record buffer */
hRec = DBL_AllocRec(hTable);

/* Let DBL_FindRec return error if not present */
DBL_Allow(DBL_Err_RecordNotFound);

/* Find the first record */
if (DBL_FindRec(hTable, hRec, "-"))
{
do
{
/* ... */

/* Get the next record */
} while (DBL_NextRec(hTable, hRec, 1));
}
DBL_FreeRec(hRec);
/* ... */
```

For more information about records and FlowFields, see the *Application Designer's Guide*.

Inserting a Record

Inserting a record is a three-step operation:

- 1 Call `DBL_InitRec` to initialize the record. This function assigns the default field values that were defined when the record layout was created in `C/SIDE`.

2 Modify the field values.

Be aware that the library does not provide range and validity checks. You must verify that the inserted data is valid.

3 After you have verified the contents of the fields, call `DBL_InsertRec` to insert the record into the table.

The database manager will ensure that the new record is automatically inserted into the correct place. The correct place is determined by the values of the fields in the primary key.

In the following example, an initialized record is inserted into the table:

```
DBL_HTABLE hTable;
DBL_HREC hRec;

/* ... */

/* Allocate memory for the record buffer */
hRec = DBL_AllocRec(hTable);

/* Initialize record */
DBL_InitRec(hTable, hRec);

/* ... assign values to fields in hRec ... */

DBL_BWT();
DBL-Allow(DBL_Err_RecordExists);
if (DBL_InsertRec(hTable, hRec))
{
    printf("Record inserted.\n");
    DBL_EWT();
}
else
{
    printf("Record NOT inserted. Record already exists.\n");
    DBL_AWT();
}

/* ... */
```

The transaction functions `DBL_BWT`, `DBL_AWT` and `DBL_EWT` ensure that all the database updates that are grouped in a series are either committed (`DBL_EWT`) or rolled back (`DBL_AWT`).

Modifying a Record

Use the `DBL_ModifyRec` function to change the field values in a record. The record structure itself cannot be changed by using any of the library functions. The record structure can only be changed in C/SIDE.

Be aware that the library does not provide range and validity checks. You must verify that the data being inserted is valid.

The following example below shows how a modified record is copied from its buffer and written to the original record in the table. The fields are changed while the record

is in the buffer, but this is not shown in this example. To see the steps in detail, refer to [Editing a Field in a Record on page 17](#).

```
DBL_HTABLE hTable;
DBL_HREC hRec;

/* ... */

/* Allocate memory for the record buffer */
hRec = DBL_AllocRec(hTable);

/* ... retrieve record to modify from the table ... */

/* ... assign values to fields in hRec ... */

DBL_BWT();
DBL-Allow(DBL_Err_RecordNotFound);
if (DBL_ModifyRec(hTable, hRec))
{
printf("Record modified\n");
DBL_EWT();
}
else
{
printf("Record NOT modified. Record not found\n");
DBL_AWT();
}

/* ... */
```

The transaction functions `DBL_BWT`, `DBL_AWT` and `DBL_EWT` ensure that all database updates grouped in a series are either committed (`DBL_EWT`) or rolled back (`DBL_AWT`).

Deleting a Record

Use `DBL_DeleteRec` to delete a record from a table. This function can remove any or all records in a table, but the table description itself can only be deleted in C/SIDE.

```
DBL_HTABLE hTable;
DBL_HREC hRec;

/* ... */

/* Allocate memory for the record buffer */
hRec = DBL_AllocRec(hTable);

/* ... retrieve record to delete from the table ... */

DBL_BWT();
DBL-Allow(DBL_Err_RecordNotFound);
if (DBL_DeleteRec(hTable, hRec))
printf("Record deleted\n");
else
{
printf("Record NOT deleted. Record not found\n");
DBL_AWT();
}

/* ... */
```



```
DBL_EWT();

/* ... */
```

The transaction functions DBL_BWT, DBL_AWT and DBL_EWT ensure that all database updates that are grouped in a series are either committed (DBL_EWT) or rolled back (DBL_AWT).

Editing a Field in a Record

Before you can edit a record, you must retrieve it from the table and have it copied to a buffer, where you can access it by using a record handle. You can then use the DBL_AssignField function to assign new values to (edit) the fields in the record.

In the following example, DBL_FindRec is first used to retrieve the record and copy it to a buffer. Then it is accessed with the hRec handle, and a new value is assigned to field number 3.

```
DBL_HTABLE hTable;
DBL_HREC hRec;

/* ... */

DBL_FindRec(hTable, hRec, "=");
DBL_AssignField(hTable, hRec, 3, DBL_FieldType(hTable, 3), "RAW",
strlen("RAW"));

DBL_BWT();
DBL_ModifyRec(hTable, hRec);
DBL_EWT();

/* ... */
```

Handling Errors and Exceptions

Errors can occur if you use the library functions incorrectly. If an error occurs, the library terminates your application. However, you can specify that some errors are allowed by using the DBL-Allow function. For more information, see DBL-Allow() on page 35.

The library function DBL-Allow enables the programmer to allow the following errors:

- DBL_Err_TableNotFound
- DBL_Err_RecordNotFound
- DBL_Err_RecordExists
- DBL_Err_KeyNotFound

These allowable errors can occur in the following library functions:

- DBL_OpenTable
- DBL_FindRec
- DBL_InsertRec
- DBL_DeleteRec
- DBL_ModifyRec

- `DBL_SetCurrentKey`

If the error that causes the function to fail has been allowed by `DBL-Allow`, the function will return 0. If it has not been allowed, the library will do the following:

- 1 Fetch the corresponding error message and call the message handler, passing the error message as a parameter. If no message handler has been set, the error message is written to standard output.
- 2 Call the exception handler.

The following routine demonstrates how to allow an unsuccessful result for a record retrieval:

```
/* ... */

/* Allow DBL_FindRec to fail */
DBL-Allow(DBL_Err_RecordNotFound);

if (DBL_FindRec(hTable, hRec, "="))
    printf("Record was found\n");
else
    printf("Record was NOT found\n");

/* ... */
```

When a library function detects an error or sends a warning, it fetches the corresponding error message and calls the default message handler, passing the message, the message type and the message code as arguments. The default message handler writes the error message to standard output.

However, you can choose to install your own message handler by using the library function `DBL_SetMessageShowHandler`. Your custom message handler can do such tasks as:

- hide particular messages
- map some messages to your own versions
- improve the formatting of the messages
- log messages to a file

Error messages passed to the message handler (and displayed by the default message handler) are retrieved from the `fin.etx` and `fin.stx` ASCII files. You can inspect the contents of these files with an ASCII editor.

After the library has detected an error and the message handler has been called, the default exception handler is called. The default exception handler simply terminates the application. You can install your own exception handler to prevent the application being terminated. Use the library function `DBL_SetExceptionHandler` to install your own exception handler.

The exception handler receives two parameters: the error code and a fatal error flag. The error code identifies the error (this has the same value as the message code in the message handler) and the fatal error flag tells you whether you are able to continue to use the library functions or if you must terminate your application.

If the error is nonfatal and you decide not to terminate your application in your exception handler, the execution is continued immediately after the library call that raised the exception.

If the error is fatal, the library will terminate the application, when you return from your exception handler.

In short the exception handler can be used to:

- save data before the application is terminated.
- continue when the errors are not fatal.

Chapter 3

A Sample Application

C/Front comes with a sample application.

The chapter contains:

- Building and Running the Sample Application

3.1 Building and Running the Sample Application

In the C/Front folder on the product DVD you will find a sample C/Front C-API program named `sample.c` (source file) and `sample.exe` (executable). You can either use the executable, or build your own by using the source file. This sample program tests the most basic C/Front functions and can be used as a source of inspiration for your own programs. It can connect to a database directly or via a server.

The Sample Application

The sample application consists of the following files:

File	Contents
<code>sample.c</code>	C/Front sample application source file.
<code>sample.exe</code>	C/Front sample application executable.
<code>sample.fbk</code>	Dynamics NAV sample database backup.
<code>sample.fdb</code>	Dynamics NAV sample database.
<code>sample.txt</code>	Text file describing how to build and run the sample application. Any last-minute changes are also described here.

You will also need the `libload.c` file – the file that contains the functions that load and unload the `cfront.dll/cfrontsql.dll`.

Building the C/Front Sample Application

- 1 Copy `libload.c` and `sample.c` to your compiler directory and `cf.h` to your include directory.
- 2 Edit `sample.c`:
Delete `#include <cf/dbl_type.h>` and `#include <cf/dbl_td.h>`. Replace them with `#include <cf.h>`
- 3 Compile `sample.c` and `libload.c`.
- 4 Link `sample.obj` and `libload.obj` to `sample.exe`.

Running the Sample Application on SQL Server

If you are running on Microsoft SQL Server you must also perform the following tasks before you can run the sample application:

- 1 Open the SQL Server Option for Microsoft Dynamics NAV and create a new database called *sample*.
- 2 Restore the backup of the sample database `sample.fbk` into this new database.

Running the Sample Application

- 1 Copy the sample application `sample.exe` to the directory where `cfront.dll/cfrontsql.dll` and `sample.fdb` are placed. This is normally the directory where C/Front is installed.

- 2 Normally, the C/Front library (`cf_front.dll/cf_frontsql.dll`) reads the registry in order to locate the Dynamics NAV DBMS system. However, if multiple Dynamics NAV systems are installed or if Dynamics NAV is not present on the system, the function `SetNavisionPath` in the `cf_front.dll/cf_frontsql.dll` library must be called specifying the path to the directory where Dynamics NAV is installed or to a directory containing the following files from a Dynamics NAV installation:

```
dbm.dll
nc_netb.dll
nc_tcp.dll
slave.exe
fin.etx
fin.stx
fin.flf
```

Alternatively these files can also be copied to the directory where the sample application and the database are stored.

- 3 You run the sample application by entering the command `sample`. But you may also enter one or more of the following parameters:

Parameter	Meaning
-d	Database name
-t	Run the exception handler test
-s	Server name
-p	Set Dynamics NAV path.
-n	Nettype – C/SIDE Database Server: tcp, netb – SQL Server: Default, Named Piped, TCP/IP Sockets, Multiprotocol.

Note

.....

If you are running on SQL Server, you must have a Windows login in order to connect to the sample application.

.....

When you enter the path to Dynamics NAV, you must enter `\\` for each `\`. For example, `C:\\Program Files\\...`

Example

If you have installed the sample application on your client computer, enter the following command to run it:

```
sample
```

If the program is started by entering the `sample` command only, the following appears on the screen during startup:

```
Company present C/Front Sample Company
Testing some table functions ..OK
Verifying create table functions ..OK
Verifying the table layout ..OK
Deleting all records ..OK
```

```
Creating test data ..OK
Verifying test data ..OK
Verifying modified test data ..OK
Testing string to/from type conversion ..OK
Testing filter functions ..OK
Testing key functions ..OK
Testing bcd functions ..OK
Testing sum functions ..OK
Database test ended
```

If the program is started with a parameter (in the case illustrated below, using `sample -t`), the text will be a little different:

```
Company present C/FRONT Sample Company
Testing some table functions ..OK
Verifying create table functions ..OK
Verifying the table layout ..OK
Deleting all records ..OK
Creating test data ..OK
Verifying test data ..OK
Verifying modified test data ..OK
Testing string to/from type conversion ..OK
Testing filter functions ..OK
Testing key functions ..OK
Testing bcd functions ..OK
Testing sum functions ..OK
Exception Handler test
TableData 2000 does not exist.
Exception Handler called with Database Error: 1001.
Database test ended
```

If you have installed the sample application on a C/SIDE Database Server you can enter the following code when you want to run the sample application:

```
sample -s"My Server" -ntcp -penter the path
```

To use CFRONT to access a database on a C/SIDE Database Server enter the following code:

```
sample -s"My Server" -ntcp -d"My database" -t -p enter the path
```


Chapter 4

The Library Functions

The functions in the C/Front function library are listed and described in this chapter. The functions are grouped according to use and then they are grouped alphabetically.

The chapter contains:

- Library Functions Grouped by Use
- Library Functions in Alphabetical Order

4.1 Library Functions Grouped by Use

Initialization and Finalization Functions

Function	Purpose
DBL_Init()	Initializes the library
DBL_Exit()	Closes the library
DBL_SetNavisionPath()	Sets the path to the Dynamics NAV files

Database Functions

Function	Purpose
DBL_ConnectServerandOpenDatabase()	Connects to a server and opens a database
DBL_ConnectServer()	Connects to a server
DBL_DisconnectServer()	Disconnects from a server
DBL_ReleaseAllObjects()	Frees all resources in C/Front
DBL_OpenDatabase()	Opens a database
DBL_CloseDatabase()	Closes a database
DBL_OpenCompany()	Opens a company
DBL_CloseCompany()	Closes a company
DBL_CompanyName()	Retrieves the current company name
DBL_NextCompany()	Scans company names
DBL_GetDatabaseName()	Tests whether a database is open and – if it is open – returns its name.
DBL_GetLanguage	Retrieves the language ID that is currently used
DBL_CheckLicenseFile()	Checks user permissions against license file
DBL_LoadLicenseFile()	Loads a license file.
DBL_GetVersion()	Gets version number of C/Front library
DBL_AddKey()	Adds keys and SumIndexFields to a table
DBL_AddTableField()	Adds a field to a table
DBL_CreateTable()	Creates a database table
DBL_CreateTableBegin()	Acquires a create table handle
DBL_CreateTableEnd()	Releases a create table handle
DBL_DeleteTable()	Deletes a table from a database
DBL_SetLanguage()	Sets the language ID
DBL_TestSysPermission()	Tests whether the current license has execute permission to a specified object
DBL_Str_Compare_Database()	Compares 2 strings in the database

Security Functions

Function	Purpose
DBL_Login()	Authorizes entry to a database
DBL_UserID()	Retrieves current user ID
DBL_UserCount()	Counts users in a database
DBL_CryptPassword()	Encrypts password
DBL_UseCodeUnitsPermissions()	Allows you to use the permissions of a codeunit

Table Functions

Function	Purpose
DBL_OpenTable()	Opens a table
DBL_CloseTable()	Closes a table
DBL_GetView()	Returns the sort, key and filters on a table
DBL_OpenTemporaryTable()	Creates a temporary table
DBL_LockTable()	Locks a table
DBL_TableCaption()	Retrieves the table caption
DBL_TableDup()	Duplicates a table
DBL_TableIsSame()	Compares two tables
DBL_TableName()	Retrieves a table name
DBL_TableNo()	Retrieves a table number
DBL_NextTable()	Scans table numbers
DBL_CalcSums()	Accumulates the sums of specified columns
DBL_SetView()	Sets the current sort, key and filters on a table

Record Functions

Function	Purpose
DBL_AllocRec()	Creates a record buffer
DBL_DupRec()	Duplicates a record
DBL_FreeRec()	Removes a record buffer
DBL_FindRec()	Finds a record
DBL_FindTopRec()	Finds the first or the last record
DBL_FindSet()	Finds a set of records
DBL_NextRec()	Scans records
DBL_InsertRec()	Inserts a record
DBL_DeleteRec()	Deletes a record
DBL_DeleteRecs()	Deletes all records in a table
DBL_ModifyRec()	Modifies a record
DBL_CopyRec()	Copies a record
DBL_CmpRec()	Compares two records
DBL_InitRec()	Initializes fields in a record
DBL_RecCount()	Counts records
DBL_RenameRec()	Renames a record
DBL_CalcFields()	Updates FlowFields in a record

Transaction Functions

Function	Purpose
DBL_BWT()	Begins a write transaction
DBL_EWT()	Ends a write transaction
DBL_AWT()	Aborts a write transaction
DBL_SelectLatestVersion()	Selects the latest data version

Field Functions

Function	Purpose
DBL_FieldCaption()	Retrieves the caption for a field in a table
DBL_FieldCount()	Counts the number of fields in record
DBL_NextField()	Scans the fields in a table
DBL_FieldLen()	Retrieves the declared length of a field
DBL_FieldNo()	Retrieves a field number
DBL_FieldName()	Retrieves a field name
DBL_FieldType()	Retrieves a field type
DBL_FieldSize()	Retrieves the field size in bytes
DBL_AssignField()	Assigns a value to a field in a record
DBL_GetFieldData()	Retrieves data from a field
DBL_GetFieldDataAddr()	Retrieves the address of field data
DBL_GetFieldDataSize()	Retrieves the size of field data
DBL_FieldDataOffset()	Retrieves the offset of a field
DBL_FieldOptionCaption()	Retrieves the option caption for a field
DBL_FieldOptionStr()	Retrieves the option string of a field
DBL_FieldClass()	Retrieves the class of a field

Key Functions

Function	Purpose
DBL_SetCurrentKey()	Sets the current key for a table
DBL_GetCurrentKey()	Retrieves the current key
DBL_KeyCount()	Counts the keys
DBL_NextKey()	Scans the keys of a table
DBL_KeySQLIndexFields()	Retrieves the SQLIndexFields of a key
DBL_KeySumFields()	Retrieves the SumIndexFields of a key

Filter Functions

Function	Purpose
DBL_SetFilter()	Sets a filter for a field
DBL_RemoveFilter()	Removes a filter from a field
DBL_GetFilter()	Retrieves the current filter
DBL_SetRange()	Sets a range filter for a field
DBL_GetRange()	Retrieves the current range filter

Conversion Functions

Function	Purpose
<code>DBL_Field_2_Str()</code>	Converts a value to a string
<code>DBL_YMD_2_Date()</code>	Converts date elements to DATE type
<code>DBL_Date_2_YMD()</code>	Converts a DATE type to date units
<code>DBL_DateFormula_2_Str()</code>	Converts a DateFormula to a string
<code>DBL_Datetime_2_Str()</code>	Converts a Datetime to a string
<code>DBL_Datetime_2_Str_Ex()</code>	Converts a Datetime to an extended string
<code>DBL_Datetime_2_YMDHMST()</code>	Converts a Datetime to years, months, days, hours, minutes, seconds and thousandths of a second
<code>DBL_Datetime_2_YMDHMST_Ex()</code>	Converts a Datetime to years, months, days, hours, minutes, seconds and thousandths of a second and allows you display it as UTC or local time
<code>DBL_Duration_2_Str()</code>	Converts a Duration to a string
<code>DBL_HMST_2_Time()</code>	Converts time elements to TIME type
<code>DBL_Time_2_HMST()</code>	Converts TIME type to time units
<code>DBL_Alpha_2_Str()</code>	Converts ALPHA type to string
<code>DBL_Str_2_Alpha()</code>	Converts string to ALPHA type
<code>DBL_Date_2_Str()</code>	Converts a DATE to a string
<code>DBL_Str_2_Date()</code>	Converts a string to a DATE
<code>DBL_Str_2_Field()</code>	Converts a string to a field value
<code>DBL_Time_2_Str()</code>	Converts TIME to string
<code>DBL_Str_2_Time()</code>	Converts string to TIME
<code>DBL_Str_2_DateFormula()</code>	Converts a string to DateFormula
<code>DBL_Str_2_Datetime()</code>	Converts a string to a Datetime
<code>DBL_Str_2_Datetime_Ex()</code>	Converts a string to an extended Datetime
<code>DBL_Str_2_Duration()</code>	Converts a string to a Duration
<code>DBL_Str_2_S64()</code>	Converts a string to a biginteger
<code>DBL_Ansi2OemBuff()</code>	Converts string from ANSI to OEM
<code>DBL_Oem2AnsiBuff()</code>	Converts string from OEM to ANSI
<code>DBL_S32_2_S64()</code>	Converts an integer to a biginteger
<code>DBL_S64_2_S32()</code>	Converts a biginteger to an integer
<code>DBL_S64_2_Str()</code>	Converts a biginteger to a string
<code>DBL_YMDHMST_2_Datetime()</code>	Converts years, months, days, hours, minutes, seconds and thousandths of a second to a Datetime
<code>DBL_YMDHMST_2_Datetime_Ex()</code>	Converts years, months, days, hours, minutes, seconds and thousandths of a second to an extended Datetime

BCD Functions

Function	Purpose
DBL_BCD_2_Str()	Converts a BCD number to a string
DBL_Str_2_BCD()	Converts a string to a BCD number
DBL_BCD_2_Double()	Converts a BCD number to a double
DBL_Double_2_BCD()	Converts a double to a BCD number
DBL_BCD_2_S32()	Converts a BCD number to an S32
DBL_S32_2_BCD()	Converts an S32 to a BCD number
DBL_BCD_IsZero()	Tests if a BCD number has a value of 0
DBL_BCD_IsNegative()	Tests if a BCD number is negative
DBL_BCD_IsPositive()	Tests if a BCD number is positive
DBL_BCD_Div()	Divides one BCD number with another BCD number
DBL_BCD_Mul()	Multiplies one BCD number by another BCD number
DBL_BCD_Add()	Adds two BCD numbers together
DBL_BCD_Sub()	Subtracts one BCD number from another BCD number
DBL_BCD_Abs()	Returns the absolute value of a BCD number
DBL_BCD_Neg()	Reverses the sign of a BCD number
DBL_BCD_Power()	Raises a BCD number to a power.
DBL_BCD_Sgn()	Returns the sign of a BCD number
DBL_BCD_Cmp()	Compares one BCD number to another BCD number
DBL_BCD_Trunc()	Truncates a BCD number
DBL_BCD_Round()	Rounds a BCD number
DBL_BCD_RoundUnit()	Rounds a BCD number to a unit
DBL_BCD_Make()	Returns a BCD number

Error-Handling and Exception-Handling Functions

Function	Purpose
<code>DBL_Allow()</code>	Specifies the error to be allowed
<code>DBL_SetExceptionHandler()</code>	Installs a custom exception handler
<code>DBL_SetMessageShowHandler()</code>	Installs custom message handler
<code>DBL_GetLastErrorCode()</code>	Retrieves code of last error

4.2 Library Functions in Alphabetical Order

This section lists all the functions in the C/Front library in alphabetical order.

DBL_AddKey()

Function	Adds keys and SumIndexFields to a table.
Category	Database function.
Syntax	<pre>void DBL_AddKey(DBL_HCREATE_TABLE hCreateTable, DBL_S32 *Key, DBL_S32 *SumIndexFields);</pre> <p>hCreateTable: A create table handle (see DBL_CreateTableBegin) Key: Zero-terminated array of the field numbers that you want to constitute the key SumIndexFields: Zero-terminated array of the field numbers for which you want SumIndexFields to be maintained</p>
Remarks	<p>The first time you call DBL_AddKey you create the primary key and the SumIndexFields that are associated with the primary key. You can then add more keys and SumIndexFields by making more AddKey calls.</p> <p>The fields (and the table itself) are not created in the database until you call DBL_CreateTable.</p>
Example	<pre>DBL_HCREATE_TABLE hCT; DBL_S32 TableNo = 50000; DBL_U8 *TableName = (DBL_U8*)"Sample Table"; DBL_S32 Key[15]; DBL_S32 SumIndexFields[15]; DBL_CreateTableBegin(&hCT, TableNo, TableName, 1); /* create table fields */ Key[0] = 10; Key[1] = 0; SumIndexFields[0] = 40; SumIndexFields[1] = 0; DBL_AddKey(hCT, Key, SumIndexFields);</pre>

DBL_AddTableField()

Function	Adds a field to a table.
Category	Database function.
Syntax	<pre>void DBL_AddTableField(DBL_HCREATE_TABLE hCreateTable, DBL_S32 FieldNo, DBL_U8 *FieldName, DBL_U16 FieldType, DBL_S16 FieldLen, DBL_U8 *OptionStr,</pre>

```
DBL_S16 FieldClass);
```

```
hCreateTable: A create table handle (see CreateTableBegin)
FieldNo: Number of the field to add
FieldName: Name of the field to add
FieldType: Type of the field to add
FieldLen: The length of the field
OptionStr: A comma-separated string of option values
FieldClass: The class of the field
```

Remarks

The `FieldType` can be one of these constants:

```
DBL_Type_STR
DBL_Type_DATE
DBL_Type_TIME
DBL_Type_BLOB
DBL_Type_BOOL
DBL_Type_S32
DBL_Type_ALPHA
DBL_Type_O32
DBL_Type_BCD
```

`FieldLen` is only relevant for fields of type `DBL_Type_STR` and `DBL_Type_ALPHA`. `FieldLen` corresponds to the *declared* length, not the actual length of a field.

The `OptionStr` should be a string like "a,b,c,d".

`FieldClass` can be one of these constants:

```
DBL_Class_Normal
DBL_Class_FlowField
DBL_Class_FlowFilter
```

`DBL_AddTableField` adds a field to a table. You must already have acquired a create table handle by calling `DBL_CreateTableBegin`. The table will not be created in the database before you call `DBL_CreateTable` on the create table handle.

You can create keys and `SumIndexFields` by using `DBL_AddKey`.

Example

```
DBL_HCREATE_TABLE hCT;
DBL_S32 TableNo = 50000;
DBL_U8 *TableName = (DBL_U8*)"Sample Table";

DBL_CreateTableBegin(&hCT, TableNo, TableName, 1);
DBL_AddTableField(hCT, 10, (DBL_U8*)"Decimal Field", DBL_Type_BCD, 0, NULL, 0);
DBL_AddTableField(hCT, 20, (DBL_U8*)"Date Field", DBL_Type_DATE, 0, NULL, 0);
DBL_AddTableField(hCT, 30, (DBL_U8*)"Time Field", DBL_Type_TIME, 0, NULL, 0);
```

DBL_AllocRec()

Function

Creates a record buffer.

Category

Record function.

Syntax	<pre>DBL_HREC DBL_AllocRec(DBL_HTABLE hTable); hTable: Handle to the table</pre>
Remarks	<p>DBL_AllocRec creates a record buffer for the specified table handle. If it is successful, a handle for the record is returned. A record buffer is just an area of memory that has the same size as a record (including virtual fields – FlowFields and FlowFilters) in the specified table. Changes to the buffer do not affect the table. You change or add table records by using DBL_InsertRec, DBL_ModifyRec or DBL_DeleteRec. If sufficient memory is not available, the function will raise an exception. Always use DBL_FreeRec to remove the record buffer created by DBL_AllocRec. Never use a C run-time function for record allocation and deallocation.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Allocate memory for record buffer */ hRec = DBL_AllocRec(hTable); /* ... */ /* Free memory occupied by record buffer */ DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL-Allow()

Function	Specifies that an error is allowed.
Category	Error function.
Syntax	<pre>void DBL-Allow(DBL_S32 ErrorCode);</pre> <p>ErrorCode can be one of these constants:</p> <pre>DBL_Err_TableNotFound DBL_Err_RecordNotFound DBL_Err_RecordExists DBL_Err_KeyNotFound</pre>
Remarks	DBL-Allow permits certain library functions to be executed after a specified error has occurred that would otherwise raise an exception. These functions all have a boolean

return value. If a call to such a function is successful, the function returns 1. If the function fails, one of two things can happen:

- 1 If you have used `DBL-Allow` to allow the error that causes the function to fail, the function will return 0.
- 2 If the error is not allowed, the function will raise an exception and call the exception handler.

For more information about exceptions, see *Handling Errors and Exceptions* on page 17.

`DBL-Allow` stores the number of the allowed error in a global variable, which is reset when the next library function is called. Always place `DBL-Allow` immediately before the function call in which the error is to be allowed. `DBL-Allow` must be invoked again if the same error is to be permitted in a subsequent function call.

Example

```
DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Allow DBL_FindRec to fail */
DBL-Allow(DBL_Err_RecordNotFound);

if (DBL_FindRec(hTable,hRec,(DBL_U8*)" -"))
printf("Record was found.\n");
else
printf("Record was NOT found.\n");

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_Alpha_2_Str()

Function	Converts an ALPHA variable to a string.
Category	Conversion function.
Syntax	<pre>void DBL_Alpha_2_Str(DBL_U8* Str, DBL_S16 StrSize, DBL_U8* Alpha); Str: Variable to receive the converted string StrSize: Size of Str in bytes, including the terminating zero Alpha: ALPHA string to be converted</pre>
Remarks	<code>DBL_Alpha_2_Str</code> converts an Alpha variable to a string and stores it in <code>Str</code> . If <code>Str</code> is not long enough to contain the converted variable, the function raises an exception.

For more information about the ALPHA variable type, see Appendix B.

```
Example      DBL_U8 Alpha[12], Str[11];

             DBL_Init();

             DBL_Str_2_Alpha(Alpha, sizeof(Alpha), "Number10");
             DBL_Alpha_2_Str(Str, sizeof(Str), Alpha);
             printf("Variable Str now contains the string value %s\n", Str);

             DBL_Exit();
```

DBL_Ansi2OemBuff

Function	Converts characters from ANSI to OEM.
Category	Conversion function.
Syntax	<pre>void DBL_Ansi2OemBuff(const DBL_U8 *Src, DBL_U8 *Dst, DBL_S32 DstSize) Src: the source Dst: the destination DstSize: the number of characters to be converted</pre>
Remarks	DBL_Ansi2OemBuff converts the character buffer from ANSI to OEM. You must specify the source buffer the destination buffer and the number of characters. This function should be used in conjunction with DBL_Oem2AnsiBuff because it can successfully convert the characters from ANSI to OEM and back again. The comparable Windows function does not always perform this conversion successfully.
Example	<pre>DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); /* Ansi buffer is allocated room for 10 characters */ DBL_U8 Ansibuff[10]; /* Oem buffer is allocated room for 5 characters */ DBL_U8 Oembuff[5]; /* Copy the string "Hi" to the Ansi buffer */ strcpy(Ansibuff, "Hi") /* Convert the two character string from ANSI to OEM */ DBL_Ansi2OemBuff(Ansibuff, Oembuff, 2); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_AssignField()

Function	Assigns a value to a field in a record.
----------	---

Category	Field function.
Syntax	<pre>void DBL_AssignField(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32 FieldNo, DBL_U16 Type, void *Data, DBL_S32 DataSize);</pre> <p>hTable: handle to the table hRec: handle to the record FieldNo: the field number Type: the type of the field Data: pointer to the data DataSize: size of the data</p>
Remarks	DBL_AssignField places the data that is pointed to by the Data pointer in the FieldNo field of hRec. Note that Data is designed as a void pointer – a pointer to any kind of data type. DataSize must be set to the size of the data in bytes (for example, as returned by the C function sizeof).
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; char s[100]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); sprintf(s,"This is some test data"); DBL_BWT(); DBL_InitRec(hTable,hRec); DBL_AssignField(hTable,hRec,10,DBL_FieldType(hTable,10), s,sizeof(s)); DBL_InsertRec(hTable,hRec); DBL_EWT(); DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_AWT()

Function	Aborts a write transaction.
Category	Transaction function.
Syntax	<pre>void DBL_AWT(void);</pre>
Remarks	DBL_AWT signals the interruption of a write transaction and undoes all of the changes that have been made in the database since DBL_BWT was issued and unlocks any locked tables. DBL_BWT must be used before DBL_AWT is called.

For more information about write transactions, see the *Application Designer's Guide*.

```

Example      DBL_HTABLE hTable;
             DBL_HREC hRec;

             DBL_Init();
             DBL_OpenDatabase("test.fdb", 2000, 0);
             DBL_OpenCompany("Test Company");
             DBL_OpenTable(&hTable, 15);
             hRec = DBL_AllocRec(hTable);

             /* Start write transaction */
             DBL_BWT();

             /* Insert and modify records using hRec and hTable */

             /* Abort write transaction */
             DBL_AWT();
             printf("Table 15 is unchanged\n");

             DBL_FreeRec(hRec);
             DBL_CloseTable(hTable);
             DBL_CloseCompany();
             DBL_CloseDatabase();
             DBL_Exit();

```

DBL_BCD_2_Double()

Function	Converts a BCD (decimal number) to a double.
Category	BCD function.
Syntax	<pre>void DBL_BCD_2_Double(DBL_DOUBLE* Dest, const DBL_BCD* Source)</pre> <p>Dest: Variable in which the converted BCD is placed Source: BCD variable to be converted</p>
Remarks	DBL_BCD_2_Double converts Source to a double and places the result in Dest.
Example	<pre> DBL_BCD b1, b2; double d1, d2; DBL_Init(); d1 = 12.56789; DBL_Double_2_BCD(&b1, d1); DBL_Double_2_BCD(&b2, d1); DBL_BCD_Round(&b1, 2); DBL_BCD_Trunc(&b2, 2); DBL_BCD_2_Double(&d1, &b1); DBL_BCD_2_Double(&d2, &b2); if ((d1 != 12.57) (d2 != 12.56)) return(-1); DBL_Exit(); </pre>

DBL_BCD_2_S32()

Function	Converts a BCD (decimal number) to an S32.
Category	BCD function.
Syntax	<pre>DBL_S32 DBL_BCD_2_S32(const DBL_BCD *Source);</pre> <p>Source: BCD variable to be converted</p>
Remarks	DBL_BCD_2_S32 converts the BCD variable Source to an S32 value, and returns this value.
Example	<pre>DBL_BCD b1; DBL_S32 s1, s2; DBL_Init(); s1 = 31415; DBL_S32_2_BCD(&b1, s1); s2 = DBL_BCD_2_S32(&b1); if (s1 != s2) return(-1); DBL_Exit();</pre>

DBL_BCD_2_Str()

Function	Converts a BCD (decimal number) to a string.
Category	BCD function.
Syntax	<pre>void DBL_BCD_2_Str(DBL_U8* Str, DBL_S16 StrSize, DBL_BCD* Bcd);</pre> <p>Str: Variable in which the converted BCD is placed StrSize: Size of Str in bytes, including the terminating zero Bcd: BCD variable to be converted</p>
Remarks	DBL_BCD_2_Str converts Bcd to a string and stores it in Str. The returned string is formatted according to the format specified in the Windows setup. This means that the following examples may yield different results, depending on the Windows setup.

Value	String
1234	"1234"
-1234	"-1234"
1234.00	"1234"

Value	String
1234.050	"1234.05"
11234.56	"11234.56"
.005	"0.005"

If Str cannot hold the converted BCD, then Str is filled with '*' characters.

Example

```
DBL_BCD Bcd;
DBL_U8 Str[11];

DBL_Init();

DBL_Str_2_BCD(&Bcd, "-1.2345");
/* Variable Bcd now contains the value -1.2345 */

DBL_BCD_2_Str(Str, sizeof(Str), &Bcd);
/* Variable Str now contains the string value "-1.2345" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_BCD_2_Str(Str, 6+1, &Bcd);
/* Variable Str now contains the string value "*****" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_Exit();
```

DBL_BCD_Abs()

Function	Converts a BCD number to the absolute value of the number.
Category	BCD function.
Syntax	<pre>void DBL_BCD_Abs(DBL_BCD *Dest);</pre> <p>Dest: the BCD number to convert</p>
Remarks	DBL_BCD_Abs converts the BCD number Dest to the absolute value of that number.

DBL_BCD_Add()

Function	Adds two BCD numbers together.
Category	BCD function.
Syntax	<pre>DBL_BCD* DBL_BCD_Add(DBL_BCD *Dest, const DBL_BCD *Source)</pre> <p>Dest: destination BCD number Source: source BCD number</p>

Remarks DBL_BCD_Add adds the BCD number Source to the BCD number Dest, and places the result in the BCD number Dest.

The function also returns the Dest BCD number. This is useful in situations where the result is only used to call yet another function, as in the following example:

```
h = DBL_BCD_Add(DBL_BCD_Add(dst, src),src1);
```

h and dst are now the same number, and that number has the value: (dst + src) + src1.

DBL_BCD_Cmp()

Function Compares two BCD numbers.

Category BCD function.

Syntax `DBL_S32 DBL_BCD_Cmp(const DBL_BCD *Left, const DBL_BCD *Right)`

Left: first (left) BCD number to compare
Right: second (right) BCD number to compare

Remarks DBL_BCD_Cmp compares the Left and Right BCD numbers. The return values are:

If	DBL_BCD_Cmp returns
Left > Right	1
Left < Right	-1
Left = Right	0

DBL_BCD_Div()

Function Divides one BCD number with another BCD number.

Category BCD function.

Syntax `DBL_BCD* DBL_BCD_Div(DBL_BCD *Dest, const DBL_BCD *Source)`

Dest: destination BCD number
Source: source BCD number

Remarks DBL_BCD_Div divides the BCD number Dest with the BCD number Source, and places the result in the BCD number Dest.

The function also returns the Dest BCD number. This is useful in situations where the result is only used to call yet another function, as in the following example:

```
h = DBL_BCD_Div(DBL_BCD_Div(dst, src),src1);
```

h and dst are now the same number, and that number has the value: (dst / src) / src1.

DBL_BCD_IsNegative()

Function	Tests whether a BCD number is negative.
Category	BCD function.
Syntax	<pre>DBL_BOOL DBL_BCD_IsNegative(const DBL_BCD *Source)</pre> <p>Source: the BCD number to test</p>
Remarks	DBL_BCD_IsNegative tests if the BCD number Source is negative. DBL_BCD_IsNegative returns TRUE if the BCD number referenced by hBcd has a value less than 0 (zero). If it does not, DBL_BCD_IsNegative returns FALSE.

DBL_BCD_IsPositive()

Function	Tests whether a BCD number is positive.
Category	BCD function.
Syntax	<pre>DBL_BOOL DBL_BCD_IsPositive(const DBL_BCD *Source)</pre> <p>Source: the BCD number to test</p>
Remarks	DBL_BCD_IsPositive tests if the BCD number Source is positive. DBL_BCD_IsPositive returns TRUE if the BCD number referenced by hBcd has a value larger than 0 (zero). If it does not, DBL_BCD_IsPositive returns FALSE.

DBL_BCD_IsZero()

Function	Tests if a BCD number has a value of 0 (zero).
Category	BCD function.
Syntax	<pre>DBL_BOOL DBL_BCD_IsZero(const DBL_BCD *Source)</pre> <p>Source: the BCD number to test</p>
Remarks	DBL_BCD_IsZero tests if the BCD number Source has a value of zero. If Source has a value of zero, DBL_BCD_IsZero returns TRUE. If it does not, DBL_BCD_IsZero returns FALSE.

DBL_BCD_Make()

Function Returns a BCD number.

Category BCD function.

Syntax `DBL_BCD* DBL_BCD_Make(DBL_BCD *Dest, DBL_S32 Kind);`

`Dest`: the BCD to make
`Kind`: what BCD number to make

Remarks `DBL_BCD_Make` creates a valid BCD number, according to the `Kind` parameter. The created BCD number is placed in `Dest` and returned by the function.

The `Kind` parameter can have the following values:

Kind	Created BCD number
<code>DBL_Make_Bcd_0</code>	0
<code>DBL_Make_Bcd_1</code>	1
<code>DBL_Make_Bcd_2</code>	2
<code>DBL_Make_Bcd_10</code>	10
<code>DBL_Make_Bcd_100</code>	100
<code>DBL_Make_Bcd_1024</code>	1024
<code>DBL_Make_Bcd_MIN</code>	The BCD with the minimum value (lowest possible)
<code>DBL_Make_Bcd_MAX</code>	The BCD number maximum value (highest possible)

DBL_BCD_Mul()

Function Multiplies two BCD numbers.

Category BCD function.

Syntax `DBL_BCD* DBL_BCD_Mul(DBL_BCD *Dest, const DBL_BCD *Source)`

`Dest`: destination BCD number
`Source`: source BCD number

Remarks `DBL_BCD_Mul` multiplies the BCD number `Dest` with the BCD number `Source`, and places the result in the BCD number `Dest`.

The function also returns the `Dest` BCD number. This is useful in situations where the result is only used to call yet another function, as in the following example:

```
h = DBL_BCD_Mul(DBL_BCD_Mul(dst, src),src1);
```

`h` and `dst` are now the same number, and that number has the value: $(dst * src) * src1$.

DBL_BCD_Neg()

Function	Reverses the sign of a BCD number.
Category	BCD function.
Syntax	<pre>void DBL_BCD_Neg(DBL_BCD *Dest);</pre> <p>Dest: BCD number to be converted</p>
Remarks	DBL_BCD_neg reverses the sign of the BCD number Dest. For example, -3 becomes 3, 4 becomes -4 and 0 remains 0.

DBL_BCD_Power()

Function	Raises a BCD number to a specified power.
Category	BCD function.
Syntax	<pre>DBL_BCD* DBL_BCD_Power(DBL_BCD *Dest, const DBL_BCD *Power);</pre> <p>Dest: the BCD number to raise to a power Power: the power to raise Dest to</p>
Remarks	<p>DBL_BCD_Power raises the BCD number Dest to the power Power, and puts the result in Dest.</p> <p>The function also returns the Dest BCD number. This is useful in situations where the result is only used to call yet another function, as in the following example:</p> <pre>h = DBL_BCD_Power(DBL_BCD_Power(dst, src), src1);</pre> <p>h and dst are now the same number, and that number has the value: (dst ** src) ** src1.</p>

DBL_BCD_Round()

Function	Rounds a BCD number.
Category	BCD function.
Syntax	<pre>void DBL_BCD_Round(DBL_BCD *Dest, DBL_S32 Cnt);</pre> <p>Dest: the BCD number to truncate Cnt: the number of digits to round Dest to</p>
Remarks	DBL_BCD_Round rounds the BCD number Dest to contain Cnt digits.

Examples:

Original BCD number	Cnt	Result
123.45	1	123.5
123.45	0	123
126.45	-1	130
153.45	-2	200
123.45	-40	0
-123.45	1	-123.5

DBL_BCD_RoundUnit()

Function Rounds a BCD number to a unit.

Category BCD function.

Syntax `void DBL_BCD_RoundUnit(DBL_BCD *Dest, const DBL_BCD *Unit, DBL_S32 How);`

Dest: the BCD number to round

Unit: the unit to use

How: how to round

Remarks DBL_BCD_RoundUnit rounds Dest according to Unit. The How parameter is used to set how rounding should occur:

If How is	DBL_BCD_RoundUnit rounds
DBL_BCD_Up	Always Up
DBL_BCD_Near	To the closest value, Up or Down
DBL_BCD_Down	Always Down

The algorithm of DBL_BCD_RoundUnit can be described like this:

- 1 The sign of Dest is saved
- 2 Dest is converted to its absolute value
- 3 Dest is divided by Unit.

If Unit is Null, the default unit of 0.01 is used. This means that Dest is rounded to 2 decimals.
- 4 The result is rounded according to How.
- 5 Dest is multiplied by Unit.
- 6 The saved sign of Dest is put back in place.

The following table shows some examples of this function:

Dest	Unit	How	Result
80	12	DBL_BCD_Up	84
80	12	DBL_BCD_Down	72
80	12	DBL_BCD_Near	84
12.5	10	DBL_BCD_Up	20

DBL_BCD_Sgn()

Function	Returns the sign of a BCD number.
Category	BCD function.
Syntax	<code>DBL_S32 DBL_BCD_Sgn(const DBL_BCD *Source);</code> Source: the BCD number to return the sign of
Remarks	DBL_BCD_Sgn return the sign of the Source BCD number:

If Source is	DBL_BCD_sgn returns
> 0	1
< 0	-1
0	0

DBL_BCD_Sub()

Function	Subtracts one BCD number from another BCD number
Category	BCD function.
Syntax	<code>DBL_BCD* DBL_BCD_Sub(DBL_BCD *Dest, const DBL_BCD *Source)</code> Dest: destination BCD number Source: source BCD number
Remarks	<p>DBL_BCD_Sub subtracts the BCD number Source from the BCD number Dest, and puts the result in the BCD number Dest.</p> <p>The function also returns the Dest BCD number. This is useful in situations where the result is only used to call yet another function, as in the following example:</p> <pre>h = DBL_BCD_Sub(DBL_BCD_Sub(dst, src), src1);</pre> <p>h and dst are now the same number, and that number has the value: (dst - src) - src1.</p>

DBL_BCD_Trunc()

Function Truncates a BCD number.

Category BCD function.

Syntax `void DBL_BCD_Trunc(DBL_BCD *Dest, DBL_S32 Cnt);`

Dest: the BCD number to truncate
Cnt: the number of digits to truncate Dest to

Remarks DBL_BCD_trunc truncates the BCD number Dest to contain Cnt digits.

Examples:

Original BCD number	Cnt	Result
123.45	1	123.4
123.45	0	123
123.45	-1	120
123.45	-2	100
123.45	-40	0
-123.45	1	-123.4

DBL_BWT()

Function Begins a write transaction.

Category Transaction function.

Syntax `void DBL_BWT(void);`

Remarks DBL_BWT marks the beginning of a set of logically related table operations (start of a transaction). The end of the transaction is signaled by a DBL_EWT or aborted with a DBL_AWT. Transactions are useful when you need to ensure that tables are not left in an inconsistent state if an operation in a set of operations fails. Multiple operations can be performed automatically with transactions.

By placing a set of operations between Begin and End transaction functions, you ensure that none of the operations are permanently recorded unless all of the operations are completed successfully.

After calling DBL_BWT, an application is allowed to modify data, using DBL_ModifyRec, etc. Calling DBL_BWT does not in itself lock the table; other users still have write access. It is only when your application begins making changes to the table or calls DBL_LockTable that the table is locked and other applications are refused access. Locked tables remain locked until either DBL_AWT or DBL_EWT is called.

For more information about write transactions, see the *Application Designer's Guide*.

```

Example
DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Start write transaction */
DBL_BWT();

/* Process hRec and hTable */

/* Commit write transaction */
DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_CalcFields()

Function	Updates FlowFields in a record.
Category	Record function.
Syntax	<pre>void DBL_CalcFields(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32* FieldList);</pre> <p>hTable: Handle to the table hRec: Handle to the record whose FlowFields are to be updated FieldList: Zero-terminated array containing the numbers of the fields in hRec to be updated</p>
Remarks	<p>DBL_CalcFields updates any FlowFields that exist in a record. FlowFields are a special C/SIDE feature that provide information from other tables in the database.</p> <p>They are also known as virtual fields because their values are not saved with the table. FlowFields are only updated when DBL_CalcFields is called. For example, FlowFields in records that are accessed with DBL_FindRec and DBL_NextRec are set to zero. DBL_CalcFields must be called to update the values in the FlowFields.</p> <p>A detailed explanation and illustration of FlowFields is available in the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_S32 Fields[11]; DBL_Init();</pre>

```

DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Update value in field 5 (a FlowField) in hRec      */
/* Causes an exception if field 5 is not a FlowField */
Fields[0] = 5;
Fields[1] = 0; /* Remember to zero-terminate strings */
DBL_CalcFields(hTable, hRec, Fields);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_CalcSums()

Function	Sums up totals for selected fields.
Category	Table function.
Syntax	<pre>void DBL_CalcSums(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32* FieldList);</pre> <p>hTable: Handle to the table hRec: Handle to the record buffer in which sums are to be placed FieldList: Zero-terminated array containing the numbers of the fields to be added up</p>
Remarks	<p>DBL_CalcSums adds up totals for specific fields (columns) in a table. The function operates only on those records that meet the conditions specified in any filters that are associated with the table handle.</p> <p>All of the fields listed in FieldList must be designated in the current key as SumIndexFields. If any of them do not meet this criteria, an exception is raised. To retrieve a list of the SumIndexFields for a given key, call DBL_KeySumFields.</p> <p>SumIndexFields are a special C/SIDE feature that give speedy access to numeric totals. SumIndexFields also work in tables that contain many thousands of records.</p> <p>For more information about SumIndexFields, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_S32 Fields[DBL_MaxSumFieldsPerKey+1]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); Fields[0] = 4; Fields[1] = 0; </pre>

```
DBL_CalcSums(hTable, hRec, Fields);
```

```
DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_CheckLicenseFile()

Function	Checks whether the license file that is currently in use contains permissions for a specified object.
Category	Database function.
Syntax	<pre>void DBL_CheckLicenseFile(DBL_S32 ObjectNo);</pre> <p>ObjectNo: number of the object to check permissions for</p>
Remarks	The permissions for the object specified by ObjectNo are checked against the license file. If the required permissions are not specified in the license file, an error (which you will have to handle) occurs.
Example	<pre>DBL_CheckLicenseFile(9110); /* C/Front license check */</pre>

DBL_CloseCompany()

Function	Closes the company that is currently open.
Category	Database function.
Syntax	<pre>void DBL_CloseCompany(void);</pre>
Remarks	DBL_CloseCompany closes the company that was opened by DBL_OpenCompany. You must close any tables that are open before calling this function.
Example	<pre>DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); /* Open company. */ /* Causes an exception if "Test Company" does not exist */ DBL_OpenCompany("Test Company"); printf("Current company is %s\n", DBL_CompanyName()); /* ... */ /* Close company */ DBL_CloseCompany();</pre>

```
DBL_CloseDatabase();
DBL_Exit();
```

DBL_CloseDatabase()

Function	Closes the database that is open.
Category	Database function.
Syntax	<code>void DBL_CloseDatabase(void);</code>
Remarks	Closes the database that was opened by <code>DBL_OpenDatabase</code> . <code>DBL_CloseDatabase</code> will raise an exception if there are any open tables or allocated records (see <code>DBL_ReleaseAllObjects</code>).
Example	<pre>DBL_Init(); /* Open database using 2000 Kb cache */ /* Causes an exception if database MY DB does not exist */ /* Causes an exception if 2000 Kb cache cannot be allocated */ DBL_OpenDatabase("MY DB.fdb", 2000, 0); /* ... */ /* Close database */ DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_CloseTable()

Function	Closes the specified table.
Category	Table function.
Syntax	<pre>void DBL_CloseTable(DBL_HTABLE hTable);</pre> <p><code>hTable</code>: Handle to the table</p>
Remarks	<p><code>DBL_CloseTable</code> deletes a handle to a table that was opened by <code>DBL_OpenTable</code> and frees the memory occupied by such things as filters. <code>hTable</code> is no longer a valid handle after this operation has been called.</p> <p>For more information about tables, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_Init();</pre>

```

DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");

/* Open table */
/* Causes an exception if table 15 does not exist */
DBL_OpenTable(&hTable, 15);

/* ... */

/* Close table */
DBL_CloseTable(hTable);

/* Open table */
DBL-Allow(DBL_Err_TableNotFound);
if (DBL_OpenTable(&hTable, 16))
{
printf("Table opened\n");
}

/* ... */

/* Close table */
DBL_CloseTable(hTable);
}
else
printf("Table does not exist\n");

DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_CmpRec()

Function	Compares two records.
Category	Record function.
Syntax	<pre> DBL_BOOL DBL_CmpRec(DBL_HTABLE hTable, const DBL_HREC hDstRec, const DBL_HREC hSrcRec); </pre> <p>hTable: handle to the table hDstRec: handle to a record hSrcRec: handle to the record to compare hDstRec against</p>
Remarks	hDstRec and hSrcRec must be handles to records from the same table. If the contents of the records are the same, the function returns TRUE. If the contents are not the same, it returns FALSE.
Example	<pre> DBL_HTABLE hTable; DBL_HREC hDstRec; DBL_HREC hSrcRec; char a[100]; char b[100]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); </pre>

```

DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hDstRec = DBL_AllocRec(hTable);
hSrcRec = DBL_AllocRec(hTable);
sprintf(a,"Some data");
sprintf(b,"Some other data");

/* Assign values to the fields of the two records. */
DBL_InitRec(hTable,hDstRec);
DBL_InitRec(hTable,hSrcRec);
DBL_AssignField(hTable,hDstRec,10,DBL_Type_STR,a,sizeof(a));
DBL_AssignField(hTable,hSrcRec,10,DBL_Type_STR,b,sizeof(b));

/* Then, compare the records: */
if (DBL_CmpRec(hTable,hDstRec,hSrcRec))
printf("The records are identical\n");
else
printf("The records are NOT identical\n");

DBL_FreeRec(hDstRec);
DBL_FreeRec(hSrcRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_CompanyName()

Function	Retrieves the name of the company that is currently open.
Category	Database function.
Syntax	<code>const DBL_U8* DBL_CompanyName(void);</code>
Remarks	<p>DBL_CompanyName returns the CompanyName of the company that was opened by DBL_OpenCompany. The returned value is a pointer to a string that contains the current CompanyName. If DBL_OpenCompany has not been called, the function returns a pointer to an empty string.</p> <p>You cannot select another CompanyName with this function. You must use DBL_CloseCompany and DBL_OpenCompany to change to another company. Companies can only be created and deleted in C/SIDE.</p>
Example	<pre> DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); /* Open company */ /* Causes an exception if "Test Company" does not exist */ DBL_OpenCompany("Test Company"); printf("Current company is %s\n", DBL_CompanyName()); /* Close company */ DBL_CloseCompany(); </pre>

```
DBL_CloseDatabase();
DBL_Exit();
```

DBL_ConnectServerandOpenDatabase()

Function Connects to a server and opens a database.

Category Database function.

Syntax

```
void DBL_ConnectServerandOpenDatabase(DBL_U8* NDBCDriverName, DBL_U8*
ServerName, DBL_U8* NetType, DBL_U8* DatabaseName, DBL_S32 CacheSize DBL_BOOL
UseCommitCache, DBL_Bool UseNTAuthentication, DBL_U8* UserID, DBL_U8*
PassWord);
```

```
NDBCDriverName: "NDBCS": The Microsoft SQL Server driver
                "NDBCN": The C/SIDE Database Server driver
```

```
ServerName: Name of the server
```

```
NetType: "Default": use the default Net Type for network communication
"Named Pipes": use Named Pipes for network communication
"TCP/IP Sockets": use TCP/IP Sockets for network communication
"Multiprotocol": use Multiprotocol for network communication
```

```
DatabaseName: Name of the database to open
```

```
CacheSize: Size of cache in KB
```

```
UseCommitCache: Whether to use CommitCache or not
```

```
UseNTAuthentication: Whether to use NT Authentication or not
```

```
UserID: Login name
```

```
Password: Password belonging to UserID
```

Remarks You must use this function with the SQL Server Option for Dynamics NAV and we recommend that you also use it with C/SIDE Database Server. It must be used with the SQL Server Option for Microsoft Dynamics NAV because SQL Server demands that you open the server, the database and provide authentication at the same time.

The Net Type you select is dependent on the server you are using:

Server:	Value:	Net Type:
SQL Server	Named Pipes	Named Pipes
	TCP/IP Sockets	TCP/IP Sockets
	Multiprotocol	Multiprotocol
	Default	Default Net Type

Server:	Value:	Net Type:
C/SIDE Database Server	tcp	TCP/IP
	tcps	TCPS
	netb	NetBIOS

The driver you select is dependent on the server you are using.

SQL Server

The server must be running when you issue this call. All succeeding calls to the database will be passed to the server, which will execute the operations.

If you are using SQL Server you still have to enter a zero value for CacheSize and UseCommitCache even though they only apply to the C/SIDE Database Server.

If you select NT Authentication (`UseNTAuthentication=1`) then you do not have to supply a user ID or a password. However, you do have to enter two empty sets of quotes ("") in order to comply with the syntax.

Issue this call again to open another database. You can only open the databases to which you have been granted permission.

C/SIDE Database Server

This function connects with a server and opens a database with a cache of the CacheSize you have specified. The server must be running when you issue this call. All succeeding calls to access the database are passed to the server, which will execute the operations.

A cache is an area of RAM that holds the results of recent disk accesses. CacheSize specifies the amount of memory assigned to the disk cache. The size depends upon which operating system is in use. As a general rule, the larger the cache, the better the performance. For more information, see the *Installation and System Management: C/SIDE Database Server* for Microsoft Dynamics NAV manual.

If you are using the C/SIDE Database Server and do not specify a server name (`ServerName=0`) the application will search for the database file on your local computer and open it, if it can be found.

If you select NT Authentication (`UseNTAuthentication=1`) then you do not have to supply a user ID or a password. However you do have to enter two empty sets of quotes ("") in order to comply with the syntax.

To close the connection to a database server, call `DisconnectServer`.

An application can only be connected to one server at a time.

Example

SQL Server

```
DBL_Init();
/* Connect to TestServer using Named Pipes and NT Authentication */

DBL_ConnectServerandOpenDatabase("NDBCS", "TestServer",
"Named Pipes", "test.fdb", 0, 0, 1, "", "");

/* Causes an exception if TestServer is not connectable*/
/* Causes an exception if database test.fdb does not exist*/
/* Causes an exception if the NT login does not give the user access to this
server*/
```



```

/*CacheSize and UseCommitCache do not apply to SQL Server*/
/*Using NT Authentication means that you do not need to enter a UserID and
Password*/

/*...*/
/* Disconnect from server */
DBL_DisconnectServer();
DBL_Exit();

```

C/SIDE Database Server

```

DBL_Init();
/* Connect to the C/SIDE Database Server "TestServer" using NetBIOS and
open testdb using 3000Kb cache, commitcache, not using NT Authentication and
therefore providing a user ID and password*/
DBL_ConnectServerandOpenDatabase("NDBCN", "TestServer", "netb", "test.fdb",
3000, 1, 0, "MyUserID", "MyPassword");

/* Causes an exception if TestServer is not connectable*/
/* Causes an exception if database test.fdb does not exist*/
/* Causes an exception if 3000 KB cannot be allocated*/
/* Causes an exception if UserID is not correct*/
/* Causes an exception if password is not correct*/

/* ...*/
/* Disconnect from server */
DBL_DisconnectServer();

DBL_Exit();

```

DBL_ConnectServer()

Function	Connects to a database server.
Category	Database function.
Syntax	<pre>void DBL_ConnectServer(DBL_U8* ServerName, DBL_U8* NetType);</pre> <p>ServerName: name of the server to connect to</p> <p>NetType: "netb": use NetBIOS for network communication "tcp": use TCP/IP for network communication</p>
Remarks	<p>The server must be running when you issue this call. All succeeding calls to access the database will be passed to the server, which will execute the operations.</p> <p>This function is applicable only in a multiuser configuration.</p> <p>To close the connections to a database server, call DBL_DisconnectServer.</p> <p>An application can be connected to only one server at a time; use DBL_DisconnectServer before connecting to another. Applications can switch between a server connection and a locally-opened database (you can alternate between</p>

DBL_ConnectServer and DBL_OpenDatabase); remember to close the existing connection before making the switch.

If an error occurs, the function will raise an exception and call the exception handler.

For more information about exceptions, see Handling Errors and Exceptions on page 17.

Example

```
DBL_Init();

/* Connect to TestServer using NetBIOS          */
/* Causes an exception if TestServer is not connectable */
DBL_ConnectServer("TestServer", "netb");

/* ...*/
/* Disconnect from server */
DBL_DisconnectServer();

DBL_Exit();
```

DBL_CopyRec()

Function

Copies a record.

Category

Record function.

Syntax

```
void DBL_CopyRec(DBL_HTABLE hTable, DBL_HREC hDstRec, const DBL_HREC
hSrcRec);
```

hTable: handle to the table
hDstRec: handle to the record to copy to
hSrcRec: handle to the record to copy from

Remarks

DBL_CopyRec copies the contents of one record to another record. hSrcRec and hDstRec must be handles to records from the same table.

Example

```
DBL_HTABLE hTable;
DBL_HREC hDstRec;
DBL_HREC hSrcRec;
char s[100];
DBL_S32 num;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hDstRec = DBL_AllocRec(hTable);
hSrcRec = DBL_AllocRec(hTable);
sprintf(s, "New data");

DBL_BWT();
/* Retrieve a record: */
DBL_FindRec(hTable, hSrcRec, (DBL_U8*)" - ")
/* And copy it: */
DBL_CopyRec(hTable, hDstRec, hSrcRec);
```

```

/* Process hDstRec, and insert it into the table: */
num = 4711;
DBL_AssignField(hTable,hDstRec,1,DBL_FieldType(hTable,1),
num,sizeof(DBL_S32));
DBL_AssignField(hTable,hDstRec,10,DBL_FieldType(hTable,10),
s,sizeof(s));
DBL_InsertRec(hTable,hDstRec);
DBL_EWT();

DBL_FreeRec(hDstRec);
DBL_FreeRec(hSrcRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_CreateTable()

Function	Creates a database table.
Category	Database function
Syntax	<pre>DBL_BOOL DBL_CreateTable(DBL_HCREATE_TABLE hCreateTable)</pre> <p>hCreateTable: Create table handle</p>
Remarks	<p>DBL_CreateTable creates a table in a Dynamics NAV database. Before using DBL_CreateTable you have to acquire a create table handle by using DBL_CreateTableBegin, and add fields and keys with DBL_AddTableField and DBL_AddKey.</p> <p>DBL_CreateTable returns TRUE if the table is created successfully and FALSE if it is not created. When creating the table fails, the error handler is called.</p> <p>If you use DBL_CreateTableEnd without using DBL_CreateTable, the table will not be created.</p>
Example	<pre> DBL_HCREATE_TABLE hCT; DBL_S32 TableNo = 50000; DBL_U8 *TableName = (DBL_U8*)"Sample Table"; DBL_CreateTableBegin(&hCT, TableNo, TableName, 1); /* add table fields, keys and SumIndexFields */ DBL_CreateTable(hCT); DBL_CreateTableEnd(hCT); </pre>

DBL_CreateTableBegin()

Function	Creates a create table handle.
Category	Database function.
Syntax	<pre>DBL_CreateTableBegin(DBL_HCREATE_TABLE *phCreateTableRef, DBL_S32 TableNo, DBL_U8 *TableName, DBL_BOOL DataPerCompany);</pre> <p>phCreateTableRef: create table handle TableNo: number of the table TableName: name of the table DataPerCompany: if FALSE, data in the table will be available to all companies in the database; if TRUE, it will only be available to the currently selected company.</p>
Remarks	<p>DBL_CreateTableBegin creates a create table handle. After you have created this handle, you can use DBL_AddTableField and DBL_AddKey to add fields and keys to the table. When you have finished defining fields and keys, you use DBL_CreateTable to create the table in C/SIDE.</p> <p>When the table has been created with DBL_CreateTable, you must close the create table handle with DBL_CreateTableEnd. If you use DBL_CreateTableEnd without using DBL_CreateTable first, the table will not be created.</p>
Example	<pre>DBL_HCREATE_TABLE hCT; DBL_S32 TableNo = 50000; DBL_U8 *TableName = (DBL_U8*)"Sample Table"; DBL_CreateTableBegin(&hCT, TableNo, TableName, 1); /* add table fields, keys and SumIndexFields */ DBL_CreateTable(hCT); DBL_CreateTableEnd(hCT);</pre>

DBL_CreateTableEnd()

Function	Closes a create table handle.
Category	Database function.
Syntax	<pre>DBL_CreateTableEnd(DBL_HCREATE_TABLE hCreateTable);</pre> <p>hCreateTable: Create table handle.</p>
Remarks	<p>DBL_CreateTableEnd closes the create table handle that hCreateTable acquired by calling DBL_CreateTableBegin.</p> <p>If you have not called DBL_CreateTable, any fields and keys you may have defined with DBL_AddTableField and DBL_AddKey will be lost.</p>

```

Example      DBL_HCREATE_TABLE hCT;
             DBL_S32      TableNo = 50000;
             DBL_U8      *TableName = (DBL_U8*)"Sample Table";

             DBL_CreateTableBegin(&hCT, TableNo, TableName, 1);

             /* add table fields, keys and SumIndexFields */

             DBL_CreateTable(hCT);
             DBL_CreateTableEnd(hCT);

```

DBL_CryptPassword()

Function	Encrypts the password.
Category	Password function
Syntax	<pre> DBL_CryptPassword(const DBL_U8 *UserID, DBL_U8 *PassWord) UserId: the user ID PassWord: the clear-text password </pre>
Remarks	DBL_CryptPassword encrypts a password, if you have supplied a user ID and a clear-text version of the password. The result is placed in PassWord.
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_U8 *UserID = (DBL_U8*)"UID"; DBL_U8 UserIDCode[12]; DBL_U8 Password[11]; DBL_U8 *EncryptedPassword; printf("Testing login functions .."); strcpy((char*)Password, "Password"); DBL_Login(UserID, Password); DBL_OpenTable(&hTable, 2000000002); /* 'User' table */ hRec = DBL_AllocRec(hTable); DBL_InitRec(hTable, hRec); DBL_BWT(); DBL_DeleteRecs(hTable); DBL_EWT(); DBL_Str_2_Alpha(UserIDCode, sizeof(UserIDCode), UserID); DBL_AssignField(hTable, hRec, 1, DBL_FieldType(hTable, 1), UserIDCode, strlen((char*)UserID)+2); DBL_AssignField(hTable, hRec, 2, DBL_FieldType(hTable, 2), Password, strlen((char*)Password)+1); DBL_BWT(); DBL_InsertRec(hTable, hRec); DBL_EWT(); DBL_InitRec(hTable, hRec); DBL_FindRec(hTable, hRec, (DBL_U8*)" - "); </pre>

```

EncryptedPassword =
(DBL_U8*)DBL_GetFieldDataAddr(hTable, hRec, 2);
DBL_CryptPassword(UserIDCode, Password);

if (0 != memcmp(EncryptedPassword, Password, strlen((char*)Password)))
{
DBL_CloseTable(hTable);
printf("Login functions \nError !");
return(-1);
}

DBL_BWT();
DBL_DeleteRecs(hTable);
DBL_EWT();
DBL_CloseTable(hTable);
printf("OK\n");

```

DBL_Date_2_Str()

Function	Converts a DATE element to a string.
Category	Conversion function
Syntax	<pre>void DBL_Date_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_DATE Date);</pre> <p>Str: the string in which to place the converted DATE StrSize: the size of the destination string Date: the DATE element to convert</p>
Remarks	DBL_Date_2_Str converts the DATE value in Date to a string. StrSize is the size of the destination string, in effect, the number of bytes to place in Str. It is your own responsibility to ensure that the converted value will not be truncated.
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_U8 resStr[50]; DBL_DATE *pDate; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Retrieve a record: */ DBL_FindRec(hTable,hSrcRec,(DBL_U8*)" -") /* Get pDate from field 20: */ pDate = (DBL_DATE*)DBL_GetFieldDataAddr(hTable,hRec,20); /* Convert pDate to a string: */ DBL_Date_2_Str(resStr,sizeof(resStr),*pDate); /* Print out the string: */ printf("Date as string: %s\n", resStr); DBL_FreeRec(hRec); </pre>

```
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_Date_2_YMD()

Function	Converts a DATE variable to year, month, day.
Category	Conversion function.
Syntax	<pre>void DBL_Date_2_YMD(DBL_S32* y, DBL_S32* m, DBL_S32* d, DBL_BOOL* Closing, DBL_DATE Date);</pre> <p>y: Variable to receive the value for year m: Variable to receive the value for month d: Variable to receive the value for day Closing: 1 if the Date value is designated as a closing date, otherwise 0 Date: DATE variable to be converted</p>
Remarks	<p>DBL_Date_2_YMD dismantles a DATE variable to create separate values for year, month and day.</p> <p>Any of the four output variables (y, m, d or Closing) can be set to NULL if they are not needed.</p> <p>If this function is called with Date=zero (undefined), an exception is raised. To prevent this occurring, test the value of the Date variable before making this call.</p>
Example	<pre>DBL_DATE Date; DBL_S32 y,m,d; DBL_BOOL c; DBL_Init(); DBL_YMD_2_Date(&Date, 1996, 5, 17, 0); /* Variable Date now contains the date May 17, 1996 */ DBL_Date_2_YMD(&y, &m, &d, &c, Date); printf("y,m,d and c now contain %d, %d, %d and %d\n",y,m,d,c); DBL_Exit();</pre>

DBL_DateFormula_2_Str()

Function	Converts a DateFormula to a string.
Category	Conversion function
Syntax	<pre>void DBL_DateFormula_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_DATEFORMULA DateFormula);</pre>

Str: the string in which to place the converted DATEFORMULA
 StrSize: the size of the destination string
 DateFormula: the DATEFROMULA to convert

Remarks DBL_DateFormula_2_Str converts the DATEFORMULA value in DateFormula to a string. StrSize is the size of the destination string, in effect, the number of bytes to place in Str. It is your own responsibility to ensure that the converted value will not be truncated.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8 resStr[50];
DBL_DATEFORMULA *pDateFormula;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Retrieve a record: */
DBL_FindRec(hTable, hSrcRec, (DBL_U8*)" -")
/* Get pDateFormula from field 20: */
pDateFormula = (DBL_DATEFORMULA*)DBL_GetFieldDataAddr(hTable, hRec, 20);
/* Convert pDateFormula to a string: */
DBL_DateFormula_2_Str(resStr, sizeof(resStr), *pDateFormula);
/* Print out the string: */
printf("DateFormula as string: %s\n", resStr);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_Datetime_2_Str()

Function Converts a Datetime to a string.

Category Conversion function

Syntax `void DBL_Datetime_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_DATETIME Datetime);`

Str: the string in which to place the converted DATETIME
 StrSize: the size of the destination string
 Datetime: the DATETIME to convert

Remarks DBL_Datetime_2_Str converts the DATETIME value in Datetime to a string. StrSize is the size of the destination string, in effect, the number of bytes to place in Str. It is your own responsibility to ensure that the converted value will not be truncated.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8 resStr[50];
DBL_DATETIME *pDatetime;

```



```

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Retrieve a record: */
DBL_FindRec(hTable,hSrcRec,(DBL_U8*)"--")
/* Get pDatetime from field 20: */
pDatetime = (DBL_DATETIME*)DBL_GetFieldDataAddr(hTable,hRec,20);
/* Convert pDatetime to a string: */
DBL_Datetime_2_Str(resStr,sizeof(resStr),*pDatetime);
/* Print out the string: */
printf("Datetime as string: %s\n", resStr);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_Datetime_2_Str_Ex()

Function	Converts a Datetime to an extended string.
Category	Conversion function
Syntax	<pre>void DBL_Datetime_2_Str_Ex(DBL_U8 *Str, DBL_S16 StrSize, DBL_DATETIME Datetime);</pre> <p>Str: the string in which to place the converted DATETIME StrSize: the size of the destination string Datetime: the DATETIME to convert</p>
Remarks	DBL_Datetime_2_Str_Ex converts the DATETIME value in Datetime to an extended string. StrSize is the size of the destination string, in effect, the number of bytes to place in Str. It is your own responsibility to ensure that the converted value will not be truncated.
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_U8 resStr[50]; DBL_DATETIME *pDatetime; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Retrieve a record: */ DBL_FindRec(hTable,hSrcRec,(DBL_U8*)"--") /* Get pDatetime from field 20: */ pDatetime = (DBL_DATETIME*)DBL_GetFieldDataAddr(hTable,hRec,20); /* Convert pDatetime to a string: */ </pre>

```

DBL_Datetime_2_Str_Ex(resStr, sizeof(resStr), *pDatetime);
/* Print out the string: */
printf("Datetime as string: %s\n", resStr);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_Datetime_2_YMDHMST()

Function	Converts a DATETIME variable to years, months, days, hours, minutes, seconds and thousandths of a second.
Category	Conversion function
Syntax	<pre> void DBL_Datetime_2_YMDHMST(DBL_s32* y, DBL_s32* m, DBL_s32* d, DBL_s32* h, DBL_s32* m, DBL_s32* s, DBL_s32* t, DBL_DATETIME Datetime); </pre> <p>Y: Variable to receive the value for years. m: Variable to receive the value for months. d: Variable to receive the value for days. h: Variable to receive the value for hours. m: Variable to receive the value for minutes. s: Variable to receive the value for seconds. t: Variable to receive the value for thousandths of a second. Datetime: the DATETIME variable to convert</p>
Remarks	<p>DBL_Datetime_2_YMDHMST dismantles a DATETIME variable and creates values for years, months, days, hours, minutes, seconds and thousandths of a second.</p> <p>Any of the output variables (ymdhmst) can be set to null, if they are not needed.</p> <p>If this function is called with DATETIME= zero (undefined), an exception is raised. To prevent this occurring, test the value of the Datetime variable before calling this function.</p>
Example	<pre> DBL_DATETIME Datetime; DBL_s32 y,m,d,h,m,s,t; DBL_INIT(); DBL_YMDHMST_2_Datetime(&Datetime, 2005, 5, 17, 14, 30, 45, 1); /* Variable Datetime now contains the datetime May 17, 2005, 14:30:45.1 */ DBL_Datetime_2_YMDHMST(&y, &m, &d, &h, &m, &s, &t, Datetime); /* Variables y,m,d,h,m,s and t now contain 2005, 5, 17, 14, 30, 45 and 1 */ printf("y,m,d,h,m,s and t now contain %d, %d, %d, %d, %d, %d and %d\n",y,m,d,h,m,s,t); DBL_Exit(); </pre>

DBL_Datetime_2_YMDHMST_Ex()

Function	Converts a DATETIME variable to years, months, days, hours, minutes, seconds and thousandths of a second
Category	Conversion function
Syntax	<pre>void DBL_Datetime_2_YMDHMST_Ex(DBL_S32 y, DBL_S32 m, DBL_S32 d, DBL_S32 h, DBL_S32 m, DBL_S32 s, DBL_S32 f, DBL_Datetime Datetime, DBL_BOOL UTC_Time);</pre> <p>Y: Variable to receive the value for years. m: Variable to receive the value for months. d: Variable to receive the value for days. h: Variable to receive the value for hours. m: Variable to receive the value for minutes. s: Variable to receive the value for seconds. t: Variable to receive the value for thousandths of a second. Datetime: the DATETIME variable to convert UTC_Time: whether or not to use UTC Time</p>
Remarks	<p>DBL_Datetime_2_YMDHMST_Ex dismantles a DATETIME variable and creates values for years, months, days, hours, minutes, seconds and thousandths of a second. It also allows you to specify if it should be displayed in UTC time or in local time.</p> <p>Any of the output variables (ymdhmst) can be set to null, if they are not needed.</p> <p>If this function is called with DATETIME= zero (undefined), an exception is raised. To prevent this occurring, test the value of the Datetime variable before calling this function.</p>
Example	<pre>DBL_DATETIME Datetime; DBL_s32 y,m,d,h,m,s,t; DBL_INIT(); DBL_YMDHMST_2_Datetime(&Datetime, 2005, 5, 17, 14, 30, 45, 1); /* Variable Datetime now contains the datetime May 17, 2005, 14:30:45.1 */ DBL_Datetime_2_YMDHMST_Ex(&y, &m, &d, &h, &m, &s, &t, Datetime, TRUE); /* Variables y,m,d,h,m,s and t now contain 2005, 5, 17, 14, 30, 45 and 1 */ printf("y,m,d,h,m,s and t now contain %d, %d, %d, %d, %d, %d and %d\n",y,m,d,h,m,s,t); DBL_Exit();</pre>

DBL_DeleteRec()

Function	Deletes a record from a table.
Category	Record function.

Syntax	<pre>DBL_BOOL DBL_DeleteRec(DBL_HTABLE hTable, DBL_HREC hRec);</pre> <p>hTable: Handle to the table hRec: Handle to the record to be deleted. hRec itself does not change.</p>
Remarks	<p>DBL_DeleteRec deletes a record from an open table. The current key and any filters bound to the table handle have no effect on this operation. The record to be deleted is identified only by the values in its primary key.</p> <p>In a multiuser environment, another application can delete the record from the table in the interval between your reading the record and your attempt to delete it. The C/SIDE database system automatically detects such an event, causing DBL_DeleteRec to raise an exception.</p> <p>To prevent this from happening, use DBL_LockTable to lock the table before reading the record. Remember, however, that the table will be locked for the time that elapses between reading and deleting the record, and that other users will therefore be unable to access it.</p> <p>For more information about table locking, see the <i>Application Designer's Guide</i>.</p> <p>If the record is successfully deleted, 1 is returned. If the record is not found in the table, two things can happen:</p> <ol style="list-style-type: none"> 1 If this result has been allowed by the function: DBL_Allow(DBL_Err_RecordNotFound), 0 is returned. 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error. <p>For more information about exceptions, see Handling Errors and Exceptions on page 17.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); DBL_BWT(); DBL_FindRec(hTable, hRec, (DBL_U8*)" - ") DBL_DeleteRec(hTable, hRec); DBL_EWT(); DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_DeleteRecs()

Function	Deletes all of the records in a table.
Category	Record function.
Syntax	<pre>DBL_DeleteRecs(DBL_HTABLE hTable)</pre> <p>hTable: handle to the table</p>
Remarks	DBL_DeleteRecs deletes all of the records in the table referenced by hTable. DBL_DeleteRecs must be used inside a transaction.
Example	<pre>DBL_HTABLE hTable; DBL_OpenTable(&hTable, 123456); DBL_BWT(); DBL_DeleteRecs(hTable); DBL_EWT(); DBL_CloseTable(hTable);</pre>

DBL_DeleteTable()

Function	Deletes a table from a database.
Category	Database function.
Syntax	<pre>DBL_BOOL DBL_DeleteTable(DBL_S32 TableNo);</pre> <p>TableNo: the number of the table to delete</p>
Remarks	<p>DBL_DeleteTable deletes the table with table number TableNo from the database. If the table was found and it could be deleted, DBL_DeleteTable returns TRUE.</p> <p>If DBL_DeleteTable returns FALSE, an error has occurred. This means that either the table could not be found or that the table was locked. When DBL_DeleteTable returns FALSE, the error handler is called.</p>

DBL_DisconnectServer()

Function	Disconnects from a database server.
Category	Database function.
Syntax	<pre>void DBL_DisconnectServer(void);</pre>

Remarks DBL_DisconnectServer disconnects an application from a database server. The connection must have been established by calling DBL_ConnectServer.

Example

```
DBL_Init();

/* Connect to TestServer using NetBIOS */
/* Causes an exception if TestServer is not connectable */
DBL_ConnectServer("TestServer", "netb");

/* Disconnect from server */
DBL_DisconnectServer();

DBL_Exit();
```

DBL_Double_2_BCD()

Function Converts a BCD (decimal number) to a double.

Category BCD function.

Syntax

```
void DBL_Double_2_BCD(DBL_BCD *Dest, DBL_DOUBLE Source)
```

Dest: Variable in which the converted double is placed
Source: double variable to be converted

Remarks DBL_Double_2_BCD converts Source to a BCD and places the result in Dest.

Example

```
DBL_BCD b1, b2;
double d1, d2;

DBL_Init();

d1 = 12.56789;
DBL_Double_2_BCD(&b1, d1);
DBL_Double_2_BCD(&b2, d1);
DBL_BCD_Round(&b1, 2);
DBL_BCD_Trunc(&b2, 2);
DBL_BCD_2_Double(&d1, &b1);
DBL_BCD_2_Double(&d2, &b2);
if ((d1 != 12.57) || (d2 != 12.56))
return(-1);

DBL_Exit();
```

DBL_DupRec()

Function Duplicates a record in a table

Category Record function

Syntax

```
DBL_HREC DBL_DupRec(DBL_HTABLE hTable, DBL_HREC hSrcRec);
```

hTable: Handle to the table
 hSrcRec: Handle to the record to be duplicated

Remarks This function returns a handle to the new record that is created.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_HREC hRecDuplicate;
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Look up first record */
/* Causes an exception if table 15 is empty */
DBL_FindRec(hTable, hRec, (DBL_U8*)"");

/* Make a copy of the first record */
hRecDuplicate = DBL_DupRec(hTable, hRec);
....

DBL_FreeRec(hRecDuplicate);
DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_Duration_2_Str()

Function Converts a Duration to a string.

Category Conversion function

Syntax `void DBL_Duration_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_DURATION);`

Str: the string in which to place the converted DURATION
 StrSize: the size of the destination string
 DateFormula: the DURATION to convert

Remarks DBL_Duration_2_Str converts the DURATION value in Duration to a string. StrSize is the size of the destination string, in effect, the number of bytes to place in Str. It is your own responsibility to ensure that the converted value will not be truncated.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8 resStr[50];
DBL_DURATION *pDuration;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");

```

```

DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Retrieve a record: */
DBL_FindRec(hTable,hSrcRec,(DBL_U8*)" -")
/* Get pDuration from field 20: */
pDuration = (DBL_DURATION*)DBL_GetFieldDataAddr(hTable,hRec,20);
/* Convert pDuration to a string: */
DBL_Duration_2_Str(resStr,sizeof(resStr),*pDuration);
/* Print out the string: */
printf("Duration as string: %s\n", resStr);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_EWT()

Function	Ends a write transaction.
Category	Transaction function.
Syntax	<code>void DBL_EWT(void);</code>
Remarks	<p>DBL_EWT signals the end of a transaction. It completes the ongoing transaction and makes the appropriate changes to the tables. All modifications that have been made to the database since DBL_BWT was called are committed, and any locked tables are unlocked.</p> <p>A call to DBL_BWT must precede a call to DBL_EWT. An application cannot abort a transaction after a DBL_EWT operation.</p> <p>For more information about write transactions, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Start write transaction */ DBL_BWT(); /* Insert and modify records */ /* Commit write transaction */ DBL_EWT(); DBL_FreeRec(hRec); DBL_CloseTable(hTable); </pre>


```
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_Exit()

Function	Closes the C/Front environment.
Category	Initializing function.
Syntax	<code>void DBL_Exit(void);</code>
Remarks	<p>DBL_Exit closes the single-user or network C/Front environment that was previously opened with DBL_Init. DBL_Exit aborts any outstanding write transactions, removes any table locks, closes any open tables and frees internal buffer areas and internal tables.</p> <p>DBL_Init must have been called before this function is used.</p>
Example	<pre>void main(int argc, char* argv[], char* envp[]) { DBL_Init(); /* A database can now be opened or */ /* a connection to a server established */ DBL_Exit(); }</pre>

DBL_Field_2_Str()

Function	Converts a value in a field to a string.
Category	Conversion function.
Syntax	<pre>void DBL_Field_2_Str(DBL_U8* Str, DBL_S16 StrSize, DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32 FieldNo);</pre> <p>Str: Variable in which the converted field will be placed StrSize: Size of Str in bytes, including the terminating zero hTable: Handle to the table hRec: Handle to the record containing the field to be converted FieldNo: Number of the field containing the value to be converted</p>
Remarks	<p>DBL_Field_2_Str converts the contents of FieldNo in hRec to a zero-terminated ASCII string and places it in Str. The field represented by FieldNo may be of any type.</p> <p>If Str is too short to hold the converted string, the converted string is truncated from the right. If FieldNo is of type integer, large integer or decimal, Str is filled with '*' characters.</p>

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8      Str[11];

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

DBL_FindRec(hTable, hRec, (DBL_U8*)"");

/* Let's assume that: */
/* Field 10 in hRec is a BCD type field containing 1.23456 */
/* Field 11 in hRec is a TEXT type field containing */
/* "This is a test" */

DBL_Field_2_Str(Str, 6+1, hTable, hRec, 10);
/* Variable Str now contains the string value "*****" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_Field_2_Str(Str, 7+1, hTable, hRec, 11);
/* Variable Str now contains the string value "This is" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FieldCaption()

Function

Returns the caption for a specific field in a table.

Category

Field function

Syntax

```
DBL_U8* DBL_FieldCaption(DBL_HTABLE hTable, DBL_S32 FieldNo);
```

hTable: Handle to the table
FieldNo: The number of the field whose caption you want returned

Remarks

This function returns the caption of the field identified by FieldNo in the table.

This function cannot be used to change the caption of the field. Field captions are defined in C/SIDE.

If no field exists with the number specified in FieldNo, the function will raise an exception. Because the field number is returned as a pointer, it (the pointer) is only valid while the handle to the table is open.

For more information about fields, see the *Application Designer's Guide*.

Example

```

DBL_HTABLE hTable;
DBL_Init();

```

```

DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
/* Retrieve information about field 3 in table 15 */
/* Causes an exception if field 3 does not exist in table 15 */
printf("Field name is %s\n", DBL_FieldName(hTable, 3));
printf("Field caption is %s\n", DBL_FieldCaption(hTable, 3));
printf("Field type is %d\n", DBL_FieldType(hTable, 3));
printf("Field size is %d\n", DBL_FieldSize(hTable, 3));
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FieldClass()

Function	Retrieves the class of a specified field.
Category	Field function.
Syntax	<pre> DBL_S16 DBL_FieldClass(DBL_HTABLE hTable, DBL_S32 FieldNo); </pre> <p>hTable: Handle to the table FieldNo: Number of the field whose class is to be determined</p>
Remarks	<p>There are three different classes of fields: Normal, FlowField or FlowFilter. DBL_FieldClass returns the class of the field with the number specified in FieldNo.</p> <p>If the number specified in FieldNo does not exist, the function will raise an exception.</p> <p>The value returned by DBL_FieldClass is one of the three constants:</p> <pre> DBL_Class_Normal DBL_Class_FlowField DBL_Class_FlowFilter </pre> <p>These constants are listed in Appendix A.</p> <p>While ordinary fields are stored in the database, FlowFields are virtual fields that contain information about other tables in the database and are not saved with the table. To update the FlowFields you must call DBL_CalcFields.</p> <p>FlowFilter fields are also virtual fields. The values in FlowFilter fields are used as parameters for calculating FlowFields.</p> <p>For more information about field classes see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_S16 Class; DBL_Init(); DBL_OpenDatabase("test-fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); </pre>

```

/* Retrieve class of field 3 */
Class = DBL_FieldClass(hTable, 3);

if (Class == DBL_Class_Normal)
printf("Field 3 is a field stored in the database\n");
else
{
printf("Field 3 is NOT a field stored in the database\n");

if (Class == DBL_Class_FlowField)
printf("because it is a FlowField\n");
else
printf("because it is a FlowFilter field\n");
}

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FieldCount()

Function	Counts the number of fields (columns) in a table.
Category	Field function.
Syntax	<pre>DBL_S16 DBL_FieldCount(DBL_HTABLE hTable);</pre> <p>hTable: Handle to the table</p>
Remarks	DBL_FieldCount retrieves the number of fields in a record in a given table. Only active fields are counted.
Example	<pre> DBL_HTABLE hTable; DBL_S16 FieldNo; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); Init("Table 15 contains %d active field(s)\n", DBL_FieldCount(hTable)); printf("These fields are numbered as follows:\n"); for (FieldNo = 0; FieldNo = DBL_NextField(hTable, FieldNo);) printf("%d\n", FieldNo); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_FieldDataOffset()

Function	Returns the offset of a specified field in a record.
Category	Field function.
Syntax	<pre>DBL_S16 DBL_FieldDataOffset(DBL_HTABLE hTable, DBL_U8 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose offset is to be retrieved</p>
Remarks	<p>DBL_FieldDataOffset returns the offset of the field with field number FieldNo in bytes, thereby indicating its position in relation to the first byte of the record. Generally, you should not use this function to assign values to or retrieve values from fields – use the DBL_AssignField and DBL_GetFieldData functions instead. This function is not expected to exist in future versions of the C/Front API, and it is only included for compatibility reasons for now.</p> <p>If FieldNo does not exist, the function will raise an exception.</p>

DBL_FieldLen()

Function	Retrieves the declared length of a specified field.
Category	Field function.
Syntax	<pre>DBL_S16 DBL_FieldLen(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose size will be retrieved</p>
Remarks	<p>DBL_FieldLen returns the declared length of FieldNo. If FieldNo does not exist, the function will raise an exception.</p> <p>While DBL_FieldSize returns the actual length of the data in a field, DBL_FieldLen returns the declared length. A text field could, for example, be declared with length 30, while the actual size of the data in the field is 8 bytes.</p> <p>For more information about C/SIDE field types and their sizes, see the <i>Application Designer's Guide</i> and Appendix A.</p>

DBL_FieldName()

Function	Retrieves the name of a specified field.
Category	Field function.
Syntax	<pre>const DBL_U8* DBL_FieldName(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre>

hTable: Handle to the table
 FieldNo: Number of the field whose name will be retrieved

Remarks DBL_FieldName returns the name of the field identified by FieldNo. This function cannot be used to change the name of the field. Field names are defined in C/SIDE.

If no field exists with the number specified in FieldNo, the function will raise an exception. Because the field name is returned as a pointer, it (the pointer) is only valid while the handle to the table is open.

For more information about fields, see the *Application Designer's Guide*.

Example

```
DBL_HTABLE hTable;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);

/* Retrieve information about field 3 in table 15          */
/* Causes an exception if field 3 does not exist in table 15 */
printf("Field name is %s\n", DBL_FieldName(hTable, 3));
printf("Field type is %d\n", DBL_FieldType(hTable, 3));
printf("Field size is %d\n", DBL_FieldSize(hTable, 3));

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_FieldNo()

Function Retrieves the number of a specified field that is identified by name.

Category Field function.

Syntax

```
DBL_S32 DBL_FieldNo(DBL_HTABLE hTable, DBL_U8* FieldName);
```

hTable: Handle to the table
 FieldName: Name of the field whose number is to be retrieved

Remarks DBL_FieldNo returns the field number of FieldName.

Each field is uniquely identified by both a number and a name. Two fields in the same table cannot have the same number or name – this is checked when fields are created in C/SIDE.

Fields are normally accessed by number because the random access used for numbers is faster than the sequential scan used for names. Therefore, you should only call DBL_FieldNo to look up the number of a field if your system does not support field numbers, and there is no alternative.

If no field exists with the name specified in `FieldName`, the function will raise an exception.

Example

```
DBL_HTABLE hTable;
DBL_S32 FieldNo;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);

/* Look up MyField in table 15 */
FieldNo = DBL_FieldNo(hTable, "TestField");

printf("TestField in table 15 has the number %d\n", FieldNo);

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_FieldOptionCaption()

Function	Returns the option caption string for a field.
Category	Field function
Syntax	<pre>DBL_U8* DBL_FieldOptionCaption(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose option caption you want returned</p>
Remarks	<p>Remarks <code>DBL_FieldOptionCaption</code> returns a string that contains the option captions for the option field identified by <code>FieldNo</code>. Only fields of type <code>DBL_Type_O32</code> have an option caption string. The string consists of a comma-separated list of the valid option captions for the field that match the valid values of the option field.</p> <p>If no field exists with the number specified in <code>FieldNo</code> or if the field is not of the <code>DBL_Type_O32</code> type, the function will raise an exception.</p> <p>This function cannot be used to change the option caption string of the field, only to retrieve it.</p> <p>Option caption strings can only be modified in C/SIDE.</p>
Example	<pre>DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Retrieve the option caption string for field 6 in table 15 */ /* Causes an exception if field 6 does not exist in table 15 */ /* Causes an exception if field 6 is not of type DBL_Type_O32 */ printf("Option caption string is %s\n", DBL_FieldOptionCaption(hTable, 6));</pre>

```

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FieldOptionStr()

Function	Retrieves the option string of a field.
Category	Field function.
Syntax	<pre> DBL_U8* DBL_FieldOptionStr(DBL_HTABLE hTable, DBL_S32 FieldNo); </pre> <p>hTable: Handle to the table FieldNo: Option field whose option string is to be retrieved</p>
Remarks	<p>DBL_FieldOptionStr returns a string that contains the options for a specified option field. Only fields of type DBL_Type_O32 have an option string. The string consists of a comma-separated list of the valid options for the field that match the valid values of the option field.</p> <p>If no field exists with the number specified in FieldNo or if the field is not of the DBL_Type_O32 type, the function will raise an exception.</p> <p>This function cannot be used to change the option string of the field, only to retrieve it. Option strings can only be modified in C/SIDE.</p> <p>For more information about fields and option strings, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Retrieve the option string for field 6 in table 15 */ /* Causes an exception if field 6 does not exist in table 15 */ /* Causes an exception if field 6 is not of type DBL_Type_O32 */ printf("Option string is %s\n", DBL_FieldOptionStr(hTable, 6)); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_FieldSize()

Function	Retrieves the size of a specified field.
Category	Field function.
Syntax	<pre>DBL_S16 DBL_FieldSize(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose size will be retrieved</p>
Remarks	<p>DBL_FieldSize returns the size of the field specified in FieldNo in bytes. If no field exists with the number specified in FieldNo, the function will raise an exception.</p> <p>For more information about the C/SIDE field types and their sizes, see the <i>Application Designer's Guide</i> and Appendix A.</p>
Example	<pre>DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Retrieve information about field 3 in table 15 */ /* Causes an exception if field 3 does not exist in table 15 */ printf("Field name is %s\n", DBL_FieldName(hTable, 3)); printf("Field type is %d\n", DBL_FieldType(hTable, 3)); printf("Field size is %d\n", DBL_FieldSize(hTable, 3)); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_FieldType()

Function	Retrieves the type of a specified field.
Category	Field function.
Syntax	<pre>DBL_U16 DBL_FieldType(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose type will be retrieved</p>
Remarks	<p>DBL_FieldType returns the type of the field specified in FieldNo. If no field exists with the number specified in FieldNo, the function will raise an exception.</p> <p>C/SIDE supports the following data types: option, boolean, integer, biginteger, decimal, text, code, date, time, BLOB, datetime, binary, dateformula, duration, GUID.</p>

For more information about the C/SIDE data types, see the *Application Designer's Guide*. The sizes of the C/SIDE data types are listed in Appendix A.

Example

```
DBL_HTABLE hTable;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);

/* Retrieve information about field 3 in table 15          */
/* Causes an exception if field 3 does not exist in table 15 */
printf("Field name is %s\n", DBL_FieldName(hTable, 3));
printf("Field type is %d\n", DBL_FieldType(hTable, 3));
printf("Field size is %d\n", DBL_FieldSize(hTable, 3));

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_FindRec()

Function

Locates a record and copies it to a buffer.

Category

Record function.

Syntax

```
DBL_BOOL DBL_FindRec(DBL_HTABLE hTable, DBL_HREC hRec, DBL_U8* SearchMethod);
```

hTable: Handle to the table.

hRec: As input: Record from which the search will begin.

As output: Record that is found. Any FlowFields associated with the record are set to zero; use DBL_CalcFields to update these fields.

SearchMethod: A string with one or more of these operators:

```
= find record equal to hRec
< find record less than hRec
> find record greater than hRec
- find first record in table
+ find last record in table
NULL means the same as =
```

An operator can only occur once. The operators + and - must be used alone.

If SearchMethod contains any of the operators =, > or <, values must be assigned to all the fields of the current key and the primary key in hRec before making this call.

Remarks

DBL_FindRec retrieves the first record that meets the criteria set by SearchMethod and the scope of any filters associated with the table handle (set by DBL_SetFilter/Range). The order in which the records are scanned is determined by the current key of the table handle (set by DBL_SetCurrentKey).

The search starts from the values in the current key fields in hRec. If the current key is not the primary key, there is a chance that several records will have the same values in

their current key fields. In such case, the values in the primary key fields of hRec are also used in the search.

If a record is found, 1 is returned. If a record is not found, two things can happen:

- 1 If this result is allowed by DBL-Allow(DBL_Err_RecordNotFound), 0 is returned.
- 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error.

For more information about exceptions, see Handling Errors and Exceptions on page 17.

Example

```
DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Look up record matching hRec */
/* Causes an exception if hRec does not exist in table 15 */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));
DBL_FindRec(hTable, hRec, (DBL_U8*)"=");

/* Look up record equal to or greater than hRec */
/* Causes an exception if such a record does not exist */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));
DBL_FindRec(hTable, hRec, (DBL_U8*)"=>");

/* Look up first record */
/* Causes an exception if table 15 is empty */
DBL_FindRec(hTable, hRec, (DBL_U8*)"=");

/* Look up last record */
/* Causes an exception if table 15 is empty */
DBL_FindRec(hTable, hRec, (DBL_U8*)"=");

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_FindSet()

Function	Finds a set of records
Category	Record function
Syntax	DBL_BOOL DBL_FindSet(DBL_HTABLE hTable, DBL_HREC hRec, DBL_BOOL ForUpdate, DBL_BOOL UpdateKey);

hTable: Handle to the table
 hRec: Handle to the record
 ForUpdate: Whether or not the records are to be updated
 UpdateKey: Whether or not a current key field is to be updated

Remarks DBL_FindSet is for looping through a set of records and can be used for updating field values. The records can only be retrieved in ascending order.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Scan all records in table 15 in ascending order */
DBL-Allow(DBL_Err_RecordNotFound);
if (DBL_FindSet(hTable, hRec, FALSE, FALSE))
do
{
} while (DBL_NextRec(hTable, hRec, 1) != 0);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FindTopRec()

Function Finds the top or the bottom record in a table.

Category Record function

Syntax `DBL_BOOL DBL_FindTopRec(DBL_HTABLE hTable, DBL_HREC hRec, DBL_BOOL First);`

hTable: Handle to the table
 hRec: Handle to the record
 First: Whether to find the first or the last record

Remarks This function allows you to find the first or the last record in a table. Enter TRUE if you want to find the first record and FALSE if you want to find the last record.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");

```

```

DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Look up first record */
/* Causes an exception if no records exist in table 15 */
DBL_FindTopRec(hTable, hRec, TRUE);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_FreeRec()

Function	Removes a record buffer.
Category	Record function.
Syntax	<pre>void DBL_FreeRec(DBL_HREC hRec);</pre> <p>hRec: Record buffer to remove</p>
Remarks	<p>DBL_FreeRec frees the memory occupied by the specified record buffer that was previously allocated by a call to DBL_AllocRec. After this operation, hRec is no longer a valid buffer.</p> <p>A call to DBL_Exit will automatically remove all the record buffers.</p>
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Allocate memory for record buffer */ hRec = DBL_AllocRec(hTable); /* ... */ /* Free memory occupied by record buffer */ DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_GetCurrentKey()

Function	Retrieves the key that is currently assigned to a table.
Category	Key function.
Syntax	<pre>DBL_S32* DBL_GetCurrentKey(DBL_HTABLE hTable);</pre> <p>hTable: Handle to the table</p>
Remarks	<p>DBL_GetCurrentKey returns a pointer to a list of the fields that make up the current key. The field list will be the same as the key that has been set by a prior call to DBL_SetCurrentKey. If DBL_SetCurrentKey has not been called, the current key is the primary key.</p>

For more information about keys, see the *Application Designer's Guide*.

Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_S32 Key[DBL_MaxFieldsPerKey+1]; DBL_S32 *Field; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Select key on field 2 as the current key for the hTable */ /* Causes an exception if there is no key on field 2 */ Key[0] = 2; Key[1] = 0; DBL_SetCurrentKey(hTable, Key); printf("The current key on hTable contains these fields:\n"); for (Field = DBL_GetCurrentKey(hTable); *Field; Field++) printf("%d\n", *Field); /* Scan all records sorted by field 2 in ascending order */ DBL-Allow(DBL_Err_RecordNotFound); if (DBL_FindRec(hTable, hRec, (DBL_U8*)" -")) do { /* Process records */ } while (DBL_NextRec(hTable, hRec, 1)); DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>
---------	--

DBL_GetDatabaseName()

Function	Returns information about whether or not a database is open, and if it is open, its name.
Category	Database function.
Syntax	<pre>DBL_BOOL DBL_GetDatabaseName(DBL_U8* DatabaseName);</pre> <p>DatabaseName: Name of the database, if a database is open</p>
Remarks	DBL_GetDatabaseName is called before opening a database to test if it is already open. This function is used with DBL_OpenDatabase, DBL_ConnectServer or DBL_ConnectServerandOpenDatabase.

Example 1

```
DBL_U8 DatabaseName[256];

DBL_Init();

/* Connect to a running database if there is one. */
/* If no database is running, use 2000 KB cache. */
DBL_OpenDatabase(NULL, 2000, 0);

if (!DBL_GetDatabaseName(DatabaseName))
{
    strcpy(DatabaseName, "test.fdb");
    /* There is no database running. */
    /* Connect to database. */
    DBL_OpenDatabase(DatabaseName, 0, 0);
}

printf("Connected to database: %s\n", DatabaseName);

/* Close database.*/
DBL_CloseDatabase();

DBL_Exit();
```

Example 2

```
DBL_U8 DatabaseName[256];

DBL_Init();

/* Connect to a running server if there is one. */
/* If no server is running, use 2000 KB cache. */
DBL_ConnectServer("TestServer", "netb");

if !DBL_GetDatabaseName(DatabaseName)
{
    strcpy(DatabaseName, "test.fdb");
    /* There is no database running*. */
    /* Connect to database. */
    DBL_OpenDatabase(DatabaseName, 0, 0);
}

printf("Connected to database: %s\n", DatabaseName);
```

```

/* Disconnect Server */
DBL_DisconnectServer();

DBL_Exit();

```

DBL_GetFieldData()

Function	Retrieves data from a field.
Category	Field function
Syntax	<pre> DBL_S32 DBL_GetFieldData(void *Dst, DBL_S32 DstSize, DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32 FieldNo); </pre> <p> Dst: pointer to the destination of the field data DstSize: amount of data to retrieve, in bytes hTable: handle to the table hRec: handle to the record to retrieve field data from FieldNo: number of the field to retrieve data from </p>
Remarks	<p>DBL_GetFieldData is the preferred way to retrieve data from a field in a record, in order to store it in a variable for further processing. Dst is designed as a void pointer, and can therefore be a pointer to any data type.</p> <p>If the value of DstSize is less than the size of the data in the field specified with FieldNo in the record of the hTable table referenced by the hRec handle, the function will raise an exception. Therefore, you must be sure that Dst has enough space to contain the data it will receive.</p> <p>DBL_GetFieldData returns the number of bytes actually retrieved – which may be less than DstSize.</p>
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; char s[100]; int i; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Retrieve a record: */ DBL_FindRec(hTable,hRec,(DBL_U8*)"") /* Retrieve contents of field 10: */ i = DBL_GetFieldData(s,100,hTable,hRec,10); /* Print out the result of the operation: */ printf("Contents of field 10: %s (%d bytes)\n",s,i); DBL_FreeRec(hRec); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); </pre>


```
DBL_Exit();
```

DBL_GetFieldDataAddr()

Function Retrieves a pointer to the data in a field.

Category Field function

Syntax `void* DBL_GetFieldDataAddr(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32 FieldNo);`

`hTable`: handle to the table

`hRec`: handle to the record of the field

`FieldNo`: the number of the field to retrieve the data address for

Remarks DBL_GetFieldDataAddr is designed to return a void pointer to the data contained in the field with the number specified in FieldNo, in the record specified by hRec, and where hTable is a handle to the table. In the application you must cast the pointer that is returned by DBL_GetFieldDataAddr to be of the data type defined for that field.

Example

```
DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_DATE *pDate;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Retrieve a record: */
DBL_FindRec(hTable, hRec, (DBL_U8*)" -")
/* Retrieve a pointer to data of field 5 */
pDate = (DBL_DATE*)DBL_GetFieldDataAddr(hTable, hRec, 5);
/* ... */

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_GetFieldDataSize()

Function Retrieves the data size of a field.

Category Field function.

Syntax `DBL_S32 DBL_GetFieldDataSize(DBL_HTABLE hTable, DBL_S32 FieldNo, const void *FieldVal);`

hTable: handle to the table
 FieldNo: number of the field to retrieve the data size for
 FieldVal: NULL pointer, or pointer to data in field

Remarks DBL_GetFieldDataSize returns the data size of a field. In most cases, this will be the same as the size of the field that was defined in C/SIDE. However, for fields with the (C/SIDE) data types Text and Code, the actual size of the data in a field may be less than the defined size, and the actual size of a BLOB field will always be different from the defined field size – which is 0(zero) – when the BLOB field has a content (BLOB fields are stored in a dedicated area of the database).

For these three data types, the number returned depends upon the FieldVal parameter. If FieldVal is a NULL pointer, the defined size is returned. If FieldVal is a pointer to the data, the actual size is returned (as retrievable by DBL_GetFieldDataAddr). For all the other data types, it doesn't matter whether FieldVal is a NULL pointer or a pointer to the field data.

Example 1

```
DBL_HTABLE hTable;
DBL_S32 i;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);

/* Get the defined size of field 5: */
i = DBL_GetFieldDataSize(hTable,5,NULL);
/* Print out the size: */
printf("The defined size of field 5 is %d\n",i);

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

Example 2

```
DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_S32 i, j;
DBL_U8 *Text;
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Get the defined size of field 10: */
i = DBL_GetFieldDataSize(hTable,10,NULL);
/* Retrieve a specific record from the table: */
DBL_FindRec(hTable,hRec,(DBL_U8*)"")
/* Retrieve a pointer to the data of field 10 */
Text = (DBL_U8*)DBL_GetFieldDataAddr(hTable,hRec,10);
/* Get the actual size of the data in field 10: */
j = DBL_GetFieldDataSize(hTable,10,Text);

/* Print out the sizes: */
printf("Sizes of field 10 are:\n");
printf("Defined: %d\n",i);
```

```
printf("Actual:  %d\n",j);
```

```
DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_GetFilter()

Function	Retrieves the filter that has been set for a given field.
Category	Filter function.
Syntax	<pre>DBL_S32 DBL_GetFilter(DBL_HTABLE hTable, DBL_S32 FieldNo, DBL_U8* FilterStr, DBL_S16 FilterStrSize);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose filter will be retrieved FilterStr: A string variable to hold filter information FilterStrSize: Size of FilterStr, including the terminating zero</p> <p>If the contents of the filter cannot fit in FilterStr, an exception is raised.</p>
Remarks	DBL_GetFilter returns the filter expression that has been set by DBL_SetFilter or DBL_SetRange for the field specified by FieldNo.
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_S16 MaxValue; DBL_U8 FilterStr[100]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Set filter on field 3 */ MaxValue = 500; DBL_SetFilter(hTable, 3, ">=200&<=%1", &MaxValue, NULL); /* Retrieve filter on field 3 */ DBL_GetFilter(hTable, 3, FilterStr, sizeof(FilterStr)); /* Variable FilterStr now contains the string ">=200&<=500" */ printf("Current filter on field 3 is %s\n", FilterStr); /* Scan records with a value in field 3 in the range 200 - 500 */ DBL-Allow(DBL_Err_RecordNotFound); if (DBL_FindRec(hTable, hRec, (DBL_U8*)"--")) do { /* Process records */ } while (DBL_NextRec(hTable, hRec, 1) != 0); DBL_FreeRec(hRec);</pre>

```

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_GetLanguage

Function	Returns the language ID of the language that is used by the current company.
Category	Database function
Syntax	DBL_S32 DBL_GetLanguage;
Remarks	This function returns the ID of the language that is used by the current database.
Example	<pre> DBL_S32 OrgLangId; DBL_S32 NewLangId = 1031; //(LangId for German) OrgLangId = DBL_GetLanguage(); //Set new language DBL_SetLanguage(NewLangId); //Reset to original language DBL_SetLanguage(OrgLangId); </pre>

DBL_GetLastErrorCode()

Function	Retrieves the code of the last error.
Category	Error function.
Syntax	DBL_S32 DBL_GetLastErrorCode(void);
Remarks	DBL_GetLastErrorCode returns the code number of the last error that you received.
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); DBL_BWT(); DBL_FindRec(hTable, hRec, (DBL_U8*) "-"); DBL_DeleteRec(hTable, hRec); </pre>

```

/* Delete record again to provoke error */
DBL_DeleteRec(hTable, hRec);

if(DBL_GetLastErrorCode()!=0)
{
/*...record not found...*/
}

DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_GetRange()

Function	Retrieves the values of a range filter for a field.
Category	Filter function.
Syntax	<pre>void DBL_GetRange(DBL_HTABLE hTable, DBL_S32 FieldNo, void* MinValue, void* MaxValue);</pre> <p>hTable: Handle to the table FieldNo: Number of the field whose range filter is to be retrieved MinValue: If set to NULL, then MinValue is not returned MaxValue: If set to NULL, then MaxValue is not returned</p>
Remarks	<p>DBL_GetRange returns the start and end values of the range filter for the field specified by FieldNo. The values are returned in MinValue and/or MaxValue, respectively. These variables must have the same size as FieldNo.</p> <p>If either value is undefined, any attempt to return them will cause an exception. Set the undefined value to NULL to prevent an exception being caused.</p> <p>DBL_GetRange can retrieve only a single interval, for example:</p> <pre>>=5 & <=8</pre> <p>Setting a range that is more complex than this will raise an exception.</p>
Example	<pre>DBL_HTABLE hTable; DBL_S16 MinValue; DBL_S16 MaxValue; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Set range filter on field 3</pre>

```

/* Equals DBL_SetFilter(hTable, 3, ">=200&<=500") */
MinValue = 200;
MaxValue = 500;
DBL_SetRange(hTable, 3, &MinValue, &MaxValue);

/* Retrieve range limits from current filter on field 3 */
DBL_GetRange(hTable, 3, &MinValue, &MaxValue);
/* Retrieve range minimum limit from current filter on field 3 */
DBL_GetRange(hTable, 3, &MinValue, NULL);
/* Retrieve range maximum limit from current filter on field 3 */
DBL_GetRange(hTable, 3, NULL, &MaxValue);

/*****/

/* Set one value filter on field 3 */
/* Equals DBL_SetFilter(hTable, 3, "=200") */
MinValue = 200;
DBL_SetRange(hTable, 3, &MinValue, NULL);

/* Retrieve range limits from current filter on field 3 */
DBL_GetRange(hTable, 3, &MinValue, &MaxValue);
printf("MinValue and MaxValue now both contain the value 200\n");

/*****/

/* Remove filter on field 3 */
/* Equals DBL_SetFilter(hTable, 3, "") */
DBL_SetRange(hTable, 3, NULL, NULL);

/* Any call to DBL_GetRange(hTable, 3, ...) now causes an */
/* exception */

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_GetVersion()

Function	Retrieves the version number of the C/Front library functions.
Category	Database function
Syntax	DBL_S32 DBL_GetVersion(void);
Remarks	This function returns the version number of the C/Front library.
Example	printf("The C/Front library version is %d\n", DBL_GetVersion());

DBL_GetView()

Function	Returns the current sort order, key and filters on a table.
Category	Table function
Syntax	<pre>void DBL_GetView(const DBL_HTABLE hTable, DBL_U8 *ViewStrBuffer, DBL_S32 ViewStrBufferSize, DBL_BOOL UseFieldNames);</pre> <p>hTable: Handle to the table ViewStrBuffer: ViewStrBufferSize: UseFieldNames: whether to use field names or not</p>
Remarks	If the UseFieldNames parameter is set to TRUE the returned string contains references to field captions in the table that the record is associated with. If the parameter is set to FALSE, field numbers are used instead.
Example	<pre>DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); DBL_U8 ViewStrBuffer[250]; DBL_GetView(hTable, ViewStrBuffer, sizeof(ViewStrBuffer), true); printf("The filter string is %s\n", ViewStrBuffer); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_GUID_2_Str

Function	Converts a GUID to a string.
Category	Conversion Function
Syntax	<pre>void DBL_GUID_2_Str(DBL_U8* Str, DBL_S16 StrSize, DBL_GUID);</pre> <p>Str: Variable to receive the converted string StrSize: Size of Str in bytes, including the terminating zero GUID: GUID to be converted</p>
Remarks	DBL_GUID_2_Str converts an GUID to a string and stores it in Str. If Str is not long enough to contain the converted variable, the function raises an exception.
Example	<pre>DBL_GUID, Str; DBL_Init();</pre>

```
DBL_Exit();
```

DBL_HMST_2_Time()

Function	Converts units of time to a TIME variable.
Category	Conversion function.
Syntax	<pre>void DBL_HMST_2_TIME(DBL_TIME* Time, DBL_S32 h, DBL_S32 m, DBL_S32 s, DBL_S32 t);</pre> <p>Time: TIME variable that will receive the converted value h: Value for the hours m: Value for the minutes s: Value for the seconds t: Value for the thousandths of a second</p>
Remarks	DBL_HMST_2_TIME combines discrete values for hours, minutes, seconds and thousandths of a second to create a TIME variable. The range of the input values is not checked – this is your responsibility!
Example	<pre>DBL_TIME Time; DBL_S32 h,m,s,t; DBL_Init(); DBL_HMST_2_TIME(&Time, 14, 23, 30, 1); /* Variable Time now contains the time 14:23:30.1 */ DBL_TIME_2_HMST(&h, &m, &s, &t, Time); /* Variables h,m,s and t now contain 14, 23, 30 and 1 */ printf("h, m, s and t now contain %d, %d, %d and %d\n",h,m,s,t); DBL_Exit();</pre>

DBL_Init()

Function	Initializes the library.
Category	Initializing function.
Syntax	<pre>DBL_S32 DBL_Init(void);</pre>

Remarks	<p>DBL_Init initializes (opens) the library by creating and initializing internal buffers and tables. Initialization includes loading the Dynamics NAV DLL-modules used by the library. An application must therefore call DBL_Init before it calls any other library function.</p> <p>If the library is successfully initialized, 0 is returned. If initialization fails, an error code is returned. This is the only library function that returns an error code.</p> <p>For more information about errors and exceptions, see Handling Errors and Exceptions on page 17.</p> <p>Once it has been successfully called, DBL_Init cannot be called again until you have closed the library by calling DBL_Exit.</p>
Example	<pre>void main(int argc, char* argv[], char* envp[]) { DBL_Init(); /* A database can now be opened or */ /* a connection to a server established */ DBL_Exit(); }</pre>

DBL_InitRec()

Function	Initializes a record.
Category	Record function.
Syntax	<pre>void DBL_InitRec(DBL_HTABLE hTable, DBL_HREC hRec);</pre> <p>hTable: Handle to the table hRec: Handle to the record to be initialized</p>
Remarks	<p>DBL_InitRec assigns default values to each field in the record buffer. The values correspond to those that were defined when the table was created in C/SIDE. Fields for which no values were defined are assigned zero values.</p> <p>After this operation has been performed, you are free to change the values in any or all of the fields before calling DBL_InsertRec to enter the record in the table. Ensure that the field(s) which make up the primary key contain values that make the contents of the total primary key unique. If the contents of the total primary key are not unique, the database manager will reject the record.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); DBL_BWT();</pre>

```

/* Initialize all fields in hRec */
DBL_InitRec(hTable, hRec);

/* Assign value to field 1 in hRec */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));

/* Insert hRec into table 15 */
DBL_InsertRec(hTable, hRec);

DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_InsertRec()

Function	Inserts a record into a table.
Category	Record function.
Syntax	<pre>DBL_BOOL DBL_InsertRec(DBL_HTABLE hTable, DBL_HREC hRec);</pre> <p>hTable: Handle to the table hRec: Handle to the record to be inserted. hRec itself does not change.</p>
Remarks	<p>DBL_InsertRec inserts a record into an open table. Use DBL_InitRec to initialize the record before assigning values to the fields. The current key and any filters that have been placed on the table handle do not effect this operation.</p> <p>A record is uniquely identified by the values of the fields in the primary key. The C/SIDE database manager inspects the primary keys in the table before inserting the new record.</p> <p>If the record is successfully inserted, 1 is returned. If a record with the same value in the primary key already exists in the table, the insertion will fail and two things can happen:</p> <ol style="list-style-type: none"> 1 If this result is allowed by DBL_Allow(DBL_Err_RecordExists), 0 is returned. 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error. <p>For more information about errors and exceptions, see Handling Errors and Exceptions on page 17.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.db", 2000, 0);</pre>

```

DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

DBL_BWT();

/* Initialize all fields in hRec */
DBL_InitRec(hTable, hRec);

/* Assign value to field 1 in hRec */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));

/* Insert hRec into table 15 */
DBL_InsertRec(hTable, hRec);

DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_KeyCount()

Function	Counts the keys that are available for a table.
Category	Key function.
Syntax	<pre>DBL_S16 DBL_KeyCount(DBL_HTABLE hTable);</pre> <p>hTable: Handle to the table</p>
Remarks	<p>DBL_KeyCount returns the number of keys that have been defined for a table. A table always has one primary key and can have one or more secondary keys. Therefore, DBL_KeyCount always returns a number greater than or equal to one. Only active keys are counted.</p> <p>For more information about keys, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_S32 *Key,Field; DBL_S16 i; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); printf("Table 15 contains %d active key(s)\n", DBL_KeyCount(hTable)); i = 0; for (Key = NULL; Key = DBL_NextKey(hTable, Key);) </pre>

```

{
i++;
printf("Key %d contains these field number(s):\n", i);

for (Field = Key; *Field; Field++)
printf("%d\n", *Field);
}

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_KeySQLIndexFields()

Function	Returns the SQLIndex fields of a specified table key.
Category	Key function
Syntax	<pre>DBL_S32 DBL_KeySQLIndexFields(DBL_HTABLE hTable, DBL_S32 *Key);</pre> <p>hTable: Handle to the table Key: Key whose SQLIndex property is to be retrieved; this parameter may represent either a primary or secondary key.</p>
Remarks	DBL_KeySQLIndexFields retrieves a list of the SQLIndex fields for a given key and for a given table. The SQLIndex property is a C/SIDE feature that defines the actual fields to be used in a SQL Index for the given table key.
Example	<pre> DBL_HTABLE hTable; DBL_S32 Key[DBL_MaxFieldsPerKey+1]; DBL_S32 *Field; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); Key[0] = 2; /* Field number 2 */ Key[1] = 0; /* Key terminator */ printf("The key defined by field 2 contains the following SQLIndex fields:\n"); for (Field = DBL_KeySQLIndexFields(hTable, Key); *Field; Field++) printf("%d\n", *Field); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_KeySumFields()

Function	Returns the SumIndexFields of a specified table key.
Category	Key function.
Syntax	<pre>DBL_S32* DBL_KeySumFields(DBL_HTABLE hTable, DBL_S32* Key);</pre> <p>hTable: Handle to the table Key: Key whose list of SumIndexFields is to be retrieved; this parameter may represent either a primary or secondary key</p>
Remarks	<p>DBL_KeySumFields retrieves a list of the SumIndexFields for a given key and for a given table. SumIndexFields are a special C/SIDE feature that permits speedy access to numeric amounts, even in tables that contain thousands of records.</p> <p>For more information about keys and SumIndexFields, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_S32 Key[DBL_MaxFieldsPerKey+1]; DBL_S32 *Field; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); Key[0] = 2; /* Field number 2 */ Key[1] = 0; /* Key terminator */ printf("The key on field 2 contains the following SumIndexFields:\n"); for (Field = DBL_KeySumFields(hTable, Key); *Field; Field++) printf("%d\n", *Field); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_LoadLicenseFile()

Function	Loads a license file.
Category	Database function.
Syntax	<pre>void DBL_LoadLicenseFile(DBL_U8* FileName);</pre> <p>FileName: license file to load.</p>

Remarks DBL_LoadLicenseFile loads the license file specified by FileName. This function must be called before establishing a connection to a database – otherwise, the current connection will be closed.

DBL_LockTable()

Function Locks a table.

Category Table function.

Syntax `void DBL_LockTable(DBL_HTABLE hTable, DBL_U32 Mode);`

hTable: Handle to the table
Mode: DBL_LockWait or DBL_LockNoWait

Remarks DBL_LockTable locks a table to prevent conflicting write operations. You can specify either a Wait or NoWait lock for the Mode parameter:

- DBL_LockWait
If another application is carrying out a transaction on the table when you issue this lock, the function suspends your operations and waits until the table is available before returning.
- DBL_LockNoWait
If another application is carrying out a transaction on the table when you issue this lock, the function raises an exception and calls the exception handler.

The C/SIDE database system uses table locking to ensure data integrity. Whenever an application begins to change data in a table (with InsertRec / ModifyRec / DeleteRec), the table is automatically locked. The lock prevents all other applications from changing data in the same table and remains active until the write transaction is ended (or aborted) with DBL_EWT or DBL_AWT.

Table locking does not prevent any authorized users from gaining read access to the table.

Because all write operations automatically lock the table in question, a call to DBL_LockTable would seem to be unnecessary. Imagine, however, a transaction in which an application wants to inspect data before possibly (though not necessarily) changing it – and have a guarantee that the data it changes has not been altered since it was read. The solution is to lock the table before reading, thereby ensuring that no other application can change the data between your reading the data and performing the possible write transaction.

The C/SIDE database system provides deadlock detection. Let us say that two applications, A and B, simultaneously want to lock the same two tables but in reverse order. Thus A locks Table 1 and waits to lock Table 2, while B locks Table 2 and waits to lock Table 1. This potentially fatal situation is called a deadlock and is automatically detected by the C/SIDE database manager. One of the applications will raise an exception and be terminated, while the other will be allowed to continue.

DBL_LockTable is only allowed within a DBL_BWT/DBL_EXT construction.

Example

```
DBL_HTABLE hTable;
DBL_HREC   hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

DBL_BWT();

/* Prevent other users from modifying table 15 */
DBL_LockTable(hTable, DBL_LockWait);

/* Retrieve hRec from table 15 */
DBL_FindRec(hTable, hRec, (DBL_U8*)"");

/* Assign value to field 2 in hRec */
DBL_AssignField(hTable, hRec, 2, DBL_FieldType(hTable, 2), "Name",
strlen("Name"));

/* Modify hRec in table 15 */
DBL_ModifyRec(hTable, hRec);

/* Commit write transaction and remove table lock */
DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_Login()

Function	Logs a user into a database.
Category	Database function.
Syntax	<pre>DBL_BOOL DBL_Login(DBL_U8* UserID, DBL_U8* PassWord);</pre> <p>UserID: Login name (see DBL_MaxUserIDLen in cf.h) PassWord: Password belonging to UserID (see DBL_MaxPassWordLen in cf.h)</p>
Remarks	<p>DBL_Login plays a double role: it controls access to tables in a multiuser environment, and it provides password protection for user verification. The function must be called if more than one user (DBL_UserCount > 0) is permitted to open the database tables.</p> <p>A successful login, however, does not ensure access to the data. Anyone can open a database and then, after logging in, inspect table descriptions, but gaining access to data tables requires further verification. The security mechanisms in C/SIDE allow any</p>

or all tables to be protected against unauthorized users. A typical user, for example, may only have read access to the tables in one company, may be able to read and write to the tables in another company and have no access at all to the tables in a third company. `DBL_Login` returns 1 for a successful login and 0 for an unsuccessful login.

User IDs are stored in an internal table in the database. The contents of this table cannot be changed by any of the functions in the library, although the current User ID can be retrieved by `DBL_UserID`. User IDs can only be created, modified and deleted within C/SIDE.

Example

```
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);

/* Test whether login is required */
if (DBL_UserCount() > 0)
{
/* Log into database */
DBL_Login("MyUserID", "MyPassWord");

printf("Current userid is %s\n", DBL_UserID());
}

/* ... */

DBL_CloseDatabase();
DBL_Exit();
```

DBL_ModifyRec()

Function	Modifies a record in a table.
Category	Record function.
Syntax	<pre>DBL_BOOL DBL_ModifyRec(DBL_HTABLE hTable, DBL_HREC hRec);</pre> <p>hTable: The handle to the table hRec: The handle to the record that is to be modified. hRec itself does not change.</p>
Remarks	<p><code>DBL_ModifyRec</code> modifies a record in the table. The record to be modified is the one identified by the values in the primary key fields in <code>hRec</code>. The current key and any filters that have been placed on the table handle have no effect on this operation.</p> <p>In a multiuser environment, another application can modify the record in the table in the interval between your reading the record and your attempting to modify it. The C/SIDE database system automatically detects such an event, causing <code>DBL_ModifyRec</code> to raise an exception.</p> <p>To prevent this from happening, use <code>DBL_LockTable</code> to lock the table before reading the record. Remember, however, that the table will be locked for the entire time that elapses between reading the record and modifying it, and other users will therefore be unable to access it.</p>

For more information about table locking, see the *Application Designer's Guide*.

Note that the library does not support range and validity checks – it is your responsibility to verify that the data you are inserting is valid.

If the record is successfully modified, 1 is returned. If the record is not found in the table, two things can happen:

- 1 If this result is allowed by the function `BL-Allow(DBL_Err_RecordNotFound)`, 0 is returned.
- 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error.

For more information about exceptions and errors, see *Handling Errors and Exceptions* on page 17.

Example

```
DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

DBL_BWT();

/* Prevent other users from modifying table 15 */
DBL_LockTable(hTable, DBL_LockWait);

/* Retrieve hRec from table 15 */
DBL_FindRec(hTable, hRec, (DBL_U8*)"");

/* Assign value to field 2 in hRec */
DBL_AssignField(hTable, hRec, 2, DBL_FieldType(hTable, 2), "Name",
strlen("Name"));

/* Modify hRec in table 15 */
DBL_ModifyRec(hTable, hRec);

/* Commit write transaction and remove table lock */
DBL_EWT();

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_NextCompany()

Function	Retrieves the company name that comes after a specified company name.
Category	Database function.

Syntax	<pre>DBL_U8* DBL_NextCompany(DBL_U8* CompanyName);</pre> <p>CompanyName: Name of a company, or a NULL pointer. Both this parameter and the result returned by the function are pointers to strings.</p>
Remarks	<p>DBL_NextCompany returns the company name that follows CompanyName. You can scan all the company names in a database, by executing DBL_NextCompany in a loop. If you call this function with CompanyName set to NULL, the first company name in the database is returned. If you then call DBL_NextCompany using this result as an argument, the function returns the second company name, and so on, until the entire list has been scanned. When the end of the list is reached, the function returns a NULL pointer.</p> <p>The company is neither opened or closed when this function is called.</p>
Example	<pre>DBL_U8* CompName; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); printf("The database contains the following companies:\n"); for (CompName = NULL; CompName = DBL_NextCompany(CompName);) { printf("%s\n", CompName); } DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_NextField()

Function	Retrieves the field number that comes after the specified field number in a table.
Category	Field function.
Syntax	<pre>DBL_S32 DBL_NextField(DBL_HTABLE hTable, DBL_S32 FieldNo);</pre> <p>hTable: Handle to the table FieldNo: A field number. If set to zero, the first field number in the record is retrieved.</p>
Remarks	<p>DBL_NextField returns the field number of the field that comes after FieldNo. If the function reaches the end of the field number list, zero is returned.</p> <p>DBL_NextField can scan the entire list of fields in a table. The scan is restricted to the active fields and excludes the inactive ones.</p> <p>For more information about active and inactive fields, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_S32 FieldNo;</pre>

```

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("test Company");
DBL_OpenTable(&hTable, 15);

printf("Table 15 contains %d active field(s)\n",
DBL_FieldCount(hTable));

printf("These fields are numbered as follows:\n");
for (FieldNo = 0; FieldNo = DBL_NextField(hTable, FieldNo);)
printf("%d\n", FieldNo);

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_NextKey()

Function	Retrieves the table key that comes after a specified table key.
Category	Key function.
Syntax	<pre>DBL_S32* DBL_NextKey(DBL_HTABLE hTable, DBL_S32* Key);</pre> <p>hTable: Handle to the table Key: A table key or a NULL pointer</p>
Remarks	<p>DBL_NextKey returns the key that comes after the specified key in the table. Both the parameter "Key" and the function result are pointers to zero-terminated char arrays that contain the numbers of the fields comprising a key.</p> <p>This function does not influence the definition or selection of the keys. Table keys are defined in C/SIDE.</p> <p>If Key is set to NULL, the first key for the table is returned. The first key is the primary key. If DBL_NextKey is then called using the first key as the argument, the second key is returned, and so on. When the function reaches the end of the key list, it returns a NULL pointer. In this way, DBL_NextKey can scan the entire list of table keys. The scan is restricted to the active keys and excludes the inactive ones.</p> <p>For more information about keys, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_HTABLE hTable; DBL_S32 *Key; DBL_S32 *Field; DBL_S16 i; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); printf("Table 15 contains %d active key(s)\n", DBL_KeyCount(hTable)); </pre>

```

i = 0;
for (Key = NULL; Key = DBL_NextKey(hTable, Key); )
{
i++;
printf("Key %d contains the following field number(s):\n", i);
for (Field = Key; *Field; Field++)
printf("%d\n", *Field);
}

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_NextRec()

Function	Steps through a specified number of records to retrieve a record.
Category	Record function.
Syntax	<pre>DBL_S16 DBL_NextRec(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S16 Step);</pre> <p>hTable: Handle to the table hRec: As input: Record from which the search will begin. As output: Record that is found. Any FlowFields associated with the record are set to zero; use DBL_CalcFields to update these fields. Step: Number of steps. If Step=0, the function has no effect. For backward movement through the table, use a negative number.</p>
Remarks	<p>DBL_NextRec locates a record that is positioned a given number of steps before or after hRec. Movement through the table is governed by the filters and by the current key that is associated with the table handle. All of the fields in hRec which will be compared to the current key must contain relevant values before this function is called.</p> <p>The function returns the number of records that have been scanned which meet the criteria set by any filters, given the current key. This value can be closer to zero than Step, depending upon the number of records in the table. If the table is empty, zero is returned and hRec remains unchanged.</p>
Example	<pre> DBL_HTABLE hTable; DBL_HREC hRec; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Scan all records in table 15 in ascending order */ DBL-Allow(DBL_Err_RecordNotFound); if (DBL_FindRec(hTable, hRec, (DBL_U8*)"-")) </pre>

```

do
{

} while (DBL_NextRec(hTable, hRec, 1) != 0);

/* Scan all records in table 15 in descending order */
DBL-Allow(DBL_Err_RecordNotFound);
if (DBL_FindRec(hTable, hRec, (DBL_U8*)"++"))
do
{

} while (DBL_NextRec(hTable, hRec, -1) != 0);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_NextTable()

Function	Returns the table number of the table that comes after a given table number.
Category	Table function.
Syntax	<pre>DBL_S32 DBL_NextTable(DBL_S32 TableNo);</pre> <p>TableNo: A number of a table. If set to zero, the first table number is retrieved.</p>
Remarks	<p>DBL_NextTable allows you to scan all of the table numbers within a database. It returns the table number that comes after TableNo – or zero when it reaches the end of the list of table numbers.</p> <p>For more information about tables, see the <i>Application Designer's Guide</i>.</p>
Example	<pre> DBL_S32 TableNo; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company") printf("The database contains the following table numbers:\n"); for (TableNo = 0; TableNo = DBL_NextTable(TableNo);) { printf("%d\n", TableNo); } DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_Oem2AnsiBuff

Function	Converts characters from OEM to ANSI.
Category	Conversion function.
Syntax	<pre>void DBL_Oem2AnsiBuff(const DBL_U8 *Src,DBL_U8 *Dst,DBL_S32 DstSize) Src: the source Dst: the destination DstSize: the number of characters to be converted</pre>
Remarks	DBL_Oem2AnsiBuff converts the character buffer from OEM to ANSI. You must specify the source buffer the destination buffer and the number of characters. This function should be used in conjunction with DBL_Ansi2OemBuff because it can successfully convert the characters from OEM to ANSI and back again. The comparable Windows function does not always perform this conversion successfully.
Example	<pre>DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); /* Oem buffer is allocated room for 10 characters */ DBL_U8 Oembuff[10] /* Ansi buffer is allocated room for 5 characters */(DBL_U8 Ansibuff[5] /* Copy the string "Hi" to the Oem buffer */ strcpy(Oembuff, "Hi") /* Convert the two character string from OEM to ANSI */ DBL_Oem2AnsiBuff(Oembuff, Ansibuff, 2); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_OpenCompany()

Function	Opens a company in an open database.
Category	Database function.
Syntax	<pre>void DBL_OpenCompany(DBL_U8* CompanyName); CompanyName: Company to open</pre>
Remarks	<p>DBL_OpenCompany allows an application to select a company and thereby open tables and access data (records) from the database.</p> <p>An application can have only one company open at a time, but it can have many tables open, provided they are in the same company.</p>

In a multiuser environment, different applications can access different companies within a single database (via a server), but each application can only have one company open at a time.

If `CompanyName` does not exist, the function raises an exception.

For more information about companies, see the *Application Designer's Guide*.

Example

```
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);

/* Open company */
/* Causes an exception if "Test Company" does not exist */

DBL_OpenCompany("Test Company");

printf("Current company is %s\n", DBL_CompanyName());

/* Close company */
DBL_CloseCompany();

DBL_CloseDatabase();
DBL_Exit();
```

DBL_OpenDatabase()

Function	Opens a database file.
Category	Database function.
Syntax	<pre>void DBL_OpenDatabase(DBL_U8* DatabaseName, DBL_S32 CacheSize, DBL_BOOL UseCommitCache);</pre> <p>DatabaseName: Database to open CacheSize: Size of cache in KB UseCommitCache: Whether to use CommitCache or not</p>
Remarks	<p>DBL_OpenDatabase opens a database with a cache of the size specified in <code>CacheSize</code> and loads the database manager. All succeeding calls to access the database are passed to the database manager, which executes the operations.</p> <p>A cache is an area of RAM that holds the results of recent disk accesses. <code>CacheSize</code> specifies the amount of memory assigned to the disk cache that is used by the database manager when it accesses the database file. The size depends upon which operating system is being used. As a general rule, the larger the cache, the better the performance.</p> <p>For more information about cache size and performance, see the <i>Installation and System Management</i> manual.</p> <p>There are no restrictions on opening a database, but access to the tables can be governed by a password. See <code>DBL_Login</code>.</p>

Close the database by calling `DBL_CloseDatabase`. An application can have only one database open at a time. Use `DBL_CloseDatabase` before opening another database. Applications can switch between a server connection and a locally-opened database (use `DBL_ConnectServerandOpenDatabase`, `DBL_ConnectServer` and `DBL_OpenDatabase`); remember to close the current connection before making the switch.

If there is an error, the function raises an exception and calls the exception handler.

For more information about exceptions and errors, see [Handling Errors and Exceptions](#) on page 17.

Example

```
DBL_Init();

/* Open database using 2000 Kb cache */
/* Causes an exception if database test.fdb does not exist */
/* Causes an exception if 2000 Kb cache cannot be allocated */
DBL_OpenDatabase("test.fdb", 2000, 0);

/* ... */

/* Close database */
DBL_CloseDatabase();

DBL_Exit();
```

DBL_OpenTable()

Function	Opens a table and creates a handle to it.
Category	Table function.
Syntax	<pre>DBL_BOOL DBL_OpenTable(DBL_HTABLE* hTablePtr, DBL_S32 TableNo);</pre> <p>hTablePtr: New handle to the table TableNo: Number of the table to be opened</p>
Remarks	<p><code>DBL_OpenTable</code> opens the table identified by <code>TableNo</code> and assigns a handle to the table. This handle can be used for future calls. The handle remains valid until <code>DBL_CloseTable</code> is invoked. You can create several handles to the same table. You can also use other library functions to set filters and to set a current key individually for each handle.</p> <p><code>DBL_OpenTable</code> will open the table even if the user (verified by <code>DBL_Login</code>) does not have permission to access the table. But the application will receive an error when the user tries to read or modify the data in the table. Only the table description (field and key layout) can be accessed, not the table data.</p> <p>If the table is successfully opened, 1 is returned. If the table does not exist, two things can happen:</p> <ol style="list-style-type: none"> 1 If this result is allowed by <code>DBL-Allow(DBL_Err_TableNot Found)</code>, 0 is returned.

- 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error.

For more information about tables, see the *Application Designer's Guide*.

Example

```
DBL_HTABLE hTable;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");

/* Open table */
/* Causes an exception if table 15 does not exist */
DBL_OpenTable(&hTable, 15);

/* Close table */
DBL_CloseTable(hTable);

/* Open table */
DBL-Allow(DBL_Err_TableNotFound);
if (DBL_OpenTable(&hTable, 16))
{
printf("Table opened\n");

/* ... */

/* Close table */
DBL_CloseTable(hTable);
}
else
printf("Table does not exist\n");

DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_OpenTemporaryTable()

Function	Creates a temporary table.
Category	Table function.
Syntax	<pre>DBL_BOOL DBL_OpenTable(DBL_HTABLE* hTablePtr, DBL_S32 TableNo);</pre> <p>hTablePtr: New handle to the table TableNo: The number of the table to be used as a template for the temporary table.</p>
Remarks	<p>DBL_OpenTemporaryTable creates a temporary table based on the table description of the "real" table with the number specified in TableNo. The temporary table can be accessed like any other table by using hTablePtr.</p> <p>You cannot perform transactions on a temporary table because it is not a part of the database. The temporary table does not exist outside the application that creates it.</p>

Consequently, it is also "private" for the application that creates it, and other users in a multi-user system cannot access it. Other than that, you can perform the same operations as on a "real" table.

The benefit of using a temporary table is that it is held in memory and this makes performing operations on it very fast. In a client/server environment, this also reduces the load on the network. You can copy records from the corresponding "real" table by using `DBL_FindRec` and `DBL_NextRec`. You cannot use `DBL_CopyRec` because the source and the destination records must be in the same table when you are using this function. When you have performed a series of operations on the records in a temporary table, you can insert these records into the "real" table by using `DBL_InsertRec` or `DBL_ModifyRec`.

DBL_RecCount()

Function	Counts the number of records in a table.
Category	Record function.
Syntax	<pre>DBL_S32 DBL_RecCount(DBL_HTABLE hTable);</pre> <p><code>hTable</code>: Handle to the table</p>
Remarks	<p><code>DBL_RecCount</code> returns the number of records that meet the conditions specified in any filters assigned to the table handle. If no filters are set, <code>DBL_RecCount</code> returns the total number of records in the table.</p> <p>This operation is very quick if the table is not filtered. Filters make movement through the table slower.</p>
Example	<pre>DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); printf("Table 15 contains %d record(s)\n", DBL_RecCount(hTable)); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_ReleaseAllObjects()

Function	Releases all of the resources in C/FRONT.
Category	Database function.

Syntax	<code>void DBL_ReleaseAllObjects(void);</code>
Remarks	<p>DBL_ReleaseAllObjects releases all of the allocated resources in C/Front. This means that all the tables are closed and all the allocated records are released.</p> <p>This function is meant to be used when you are handling errors, where it is desirable to have all of the resources released at once.</p> <p>The database is not closed, and any open companies are not closed either.</p> <p>If all of the resources are not released, a call to DBL_OpenDatabase or DBL_CloseDatabase will raise an exception.</p>

DBL_RemoveFilter()

Function	Removes all the filters that have been applied to a specified table.
Category	Filter function.
Syntax	<pre>void DBL_RemoveFilter(DBL_HTABLE hTable);</pre> <p>hTable: Handle to the table</p>
Remarks	<p>DBL_RemoveFilter removes all the filters that have been applied (with function DBL_SetFilter or DBL_SetRange) to the fields of the table specified by hTable.</p> <p>If no filters have been assigned the result is the same.</p> <p>For more information about filter syntax and relational operators, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_S16 MinValue; DBL_S16 MaxValue; DBL_U32 RecCount; DBL_U8 FilterStr[100]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); RecCount = DBL_RecCount(hTable); printf("\nRecord count without filters: %d", RecCount); /* Set filter on field 3 */ DBL_SetFilter(hTable, 3, ">=200&<=500", NULL); RecCount = DBL_RecCount(hTable); printf("\nRecord count with filter on field 3: %d", RecCount); /* Set filter on field 4 */ MaxValue = 20; MaxValue = 50; DBL_SetRange(hTable, 4, &MinValue, &MaxValue); RecCount = DBL_RecCount(hTable);</pre>

```

printf("\nRecord count with filters on fields 3 and 4: %d", RecCount);

/* Remove filters on all fields */
DBL_RemoveFilter(hTable);
RecCount = DBL_RecCount(hTable);
printf("\nRecord count after all filters are removed: %d", RecCount);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_RenameRec()

Function	Renames the primary key of a record in a table.
Category	Record function
Syntax	<pre> DBL_BOOL DBL_RenameRec(hTable,hNewRec,hOldRec); hTable: Handle to the table hNewRec: Handle to the record with the new primary key hOldRec: Handle to the original record </pre>
Remarks	<p>This function renames the primary key of a record and the return value tells you whether or not the primary key of the record was renamed.</p> <p>The system typically returns FALSE if the record does not exist or if you do not have write permission to the table.</p> <p>In a multiuser environment, another application can rename the record in the table in the interval between your reading the record and your attempting to rename the primary key. The C/SIDE database system automatically detects such an event, causing DBL_RenameRec to raise an exception. To prevent this from happening, use DBL_LockTable to lock the table before reading the record. Remember, however, that the table will be locked for the time that elapses between reading the record and renaming it, and that other users will therefore be unable to access it.</p>

DBL_SelectLatestVersion()

Function	Selects the latest data version.
Category	Database operation
Syntax	<pre> void DBL_SelectLatestVersion(void); </pre>
Remarks	<p>DBL_SelectLatestVersion accesses the newest version of the data in a database. All subsequent database operations will be performed on this version of the data. In a single-user environment, this function has no effect, because the application always accesses the newest version – there are no other active applications creating new versions.</p>

For more information about database versions, see the *Application Designer's Guide*.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

/* Retrieve hRec from my data version */
DBL_FindRec(hTable, hRec, (DBL_U8*)"");
printf("hRec was found\n");

/* Another application connected to the database/server */
/* and deleted hRec */
/*...
DBL_BWT();
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));
DBL_DeleteRec(hTable, hRec);
DBL_EWT();
...
*****/

/* Retrieve hRec again from my data version */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));
DBL_FindRec(hTable, hRec, (DBL_U8*)"");
printf("hRec was found\n");

/* Select the latest public version to be my data version */
DBL_SelectLatestVersion();

/* Retrieve hRec from my data version */
DBL_AssignField(hTable,hRec,1,DBL_FieldType(hTable,1),"100",
strlen("100"));
DBL-Allow(DBL_Err_RecordNotFound);
if (DBL_FindRec(hTable, hRec, (DBL_U8*)""))
printf("Record still exists\n");
else
printf("Record has been deleted by another application\n");

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_S32_2_BCD()

Function	Converts an S32 variable to a BCD (decimal number).
Category	Conversion function.
Syntax	<pre>void DBL_S32_2_BCD(DBL_BCD *Dest, DBL_S32 Source);</pre> <p>Dest: Variable in which the converted S32 variable is placed Source: S32 variable to be converted</p>
Remarks	DBL_S32_2_BCD converts Source to a BCD and places the result in Dest.
Example	<pre>DBL_BCD b1; DBL_S32 s1, s2; DBL_Init(); s1 = 31415; DBL_S32_2_BCD(&b1, s1); s2 = DBL_BCD_2_S32(&b1); if (s1 != s2) return(-1); DBL_Exit();</pre>

DBL_S32_2_S64()

Function	Converts an S32 variable (integer) to an S64 value (biginteger).
Category	BCD function.
Syntax	<pre>void DBL_S32_2_S64(DBL_S64 *Dest, DBL_S32 Source);</pre> <p>Dest: Variable in which the converted S32 variable is placed Source: The S32 variable to be converted</p>
Remarks	DBL_S32_2_S64 converts the integer in Source to a biginteger and places the result in Dest.
Example	<pre>DBL_S64 b1, b2; DBL_S32 i1, i2; DBL_Str_2_S64(&b1, "12345"); DBL_Str_2_S64(&b2, "98765432100"); DBL_S64_2_S32(&i1, &b1); printf("i1 = %i", i1); DBL_S64_2_S32(&i2, &b2); /* Will return -2147483648 which indicates an undefined S32 number */ printf("i2 = %i", i2);</pre>

```
DBL_S32_2_S64(&b2, i1)
```

DBL_S64_2_S32()

Function	Converts an S64 variable (biginteger) to an S32 value (integer).
Category	Conversion function.
Syntax	<pre>void DBL_S64_2_S32(DBL_S32 *Dest, DBL_S64 Source);</pre> <p>Dest: Variable in which the converted S64 variable is placed Source: The S64 variable to be converted</p>
Remarks	<p>DBL_S64_2_S32 converts the biginteger in Source to an integer and places the result in Dest.</p> <p>This function can only return valid integers as long as the biginteger contains values that do not exceed the value range of an integer. If the biginteger exceeds the value range of an integer, the function returns -2147483648 which indicates an undefined integer.</p>
Example	<pre>DBL_S64 b1, b2; DBL_S32 i1, i2; DBL_Str_2_S64(&b1, "12345"); DBL_Str_2_S64(&b2, "98765432100"); DBL_S64_2_S32(&i1, &b1); printf("i1 = %i", i1); DBL_S64_2_S32(&i2, &b2); /* Will return -2147483648 which indicates an undefined S32 number */ printf("i2 = %i", i2); DBL_S32_2_S64(&b2, i1)</pre>

DBL_S64_2_Str()

Function	Converts a biginteger to a string.
Category	Conversion function
Syntax	<pre>void DBL_S64_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_S64 *S64Src);</pre> <p>Str: The string variable to place the converted value in StrSize: The size of the string S64Src: The biginteger to be converted</p>
Remarks	This function converts a biginteger to a string and places the result in Str.

```

Example      DBL_S64    bl;
             DBL_U8     Str[50];
             DBL_Str_2_S64(&bl, "12345");
             DBL_S64_2_Str(Str, sizeof(Str), &bl);
             printf("The value of the biginteger is %s", Str);

```

DBL_SetCurrentKey()

Function Sets the current key for a table handle.

Category Key function.

Syntax `DBL_BOOL DBL_SetCurrentKey(DBL_HTABLE hTable, DBL_S32* Key);`

`hTable`: Handle to the table
`Key`: Desired key or a NULL pointer

Remarks `DBL_SetCurrentKey` assigns a specified key to a table handle. The key becomes the current key and is used by `DBL_FindRec`, `DBL_NextRec` and other functions until another key is selected. Use `DBL_NextKey` to scan the list of keys for the table to find out which keys are available. Only active keys will be retrieved.

The primary key of the table is the current key, until `DBL_SetCurrentKey` is called. When a secondary key is the current key, you can make the primary key the current key again by calling `DBL_SetCurrentKey` with `Key` set to NULL.

If a new current key is successfully assigned to the table handle, 1 is returned. If the requested key does not exist, two things can happen:

- 1 If this result is allowed by the `DBL-Allow(DBL_Err_KeyNotFound)`, 0 is returned.
- 2 If the result is not allowed, the function will raise an exception and call the exception handler with an error.

For more information about exceptions and errors, see [Handling Errors and Exceptions](#) on page 17.

For more information about keys, see the *Application Designer's Guide*.

```

Example      DBL_HTABLE hTable;
             DBL_HREC   hRec;
             DBL_S32    Key[DBL_MaxFieldsPerKey+1];
             DBL_S32    *Field;

             DBL_Init();
             DBL_OpenDatabase("test.fdb", 2000, 0);
             DBL_OpenCompany("Test Company");
             DBL_OpenTable(&hTable, 15);
             hRec = DBL_AllocRec(hTable);

             /* Select key defined for field 2 as current key for the hTable */
             /* handle. Causes an exception if table 15 does not have a      */
             /* key on field 2                                              */
             Key[0] = 2;

```



```

Key[1] = 0;
DBL_SetCurrentKey(hTable, Key);

printf("The current key on hTable contains these fields:\n");
for (Field = DBL_GetCurrentKey(hTable); *Field; Field++)
printf("%d\n", *Field);

/* Scan all records sorted by field 2 in ascending order */
DBL_Allow(DBL_Err_RecordNotFound);
if (DBL_FindRec(hTable, hRec, (DBL_U8*)" -"))
do
{
} while (DBL_NextRec(hTable, hRec, 1));

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_SetExceptionHandler()

Function	Installs a user-written exception handler.
Category	Exception-handling function.
Syntax	<pre>void* DBL_SetExceptionHandler(DBL_pFuncExceptionHandler ExceptionHandler);</pre> <p>ExceptionHandler: The function to be installed as the exception handler for the library. If set to NULL, the default exception handler is restored.</p>
Remarks	This function installs ExceptionHandler as the exception handler that is used by the library. DBL_SetExceptionHandler returns the address of the previous exception handler. If you want to reinstall the default exception handler later, you must store this address, and use it in a call to DBL_SetExceptionHandler. Installing another handler, for example, the default one, is also the only way to disable a customized exception handler.
Example	<pre> void main(DBL_S16 argc, DBL_U8 *argv[], DBL_U8 *envp[]) { /* ... */ DBL_SetExceptionHandler(My_ExceptionHandler); /* ... */ } void DBL_CDECL My_ExceptionHandler(DBL_S32 ErrorCode, DBL_BOOL IsFatal) { char *Fatal = (IsFatal) ? " Fatal" : ""; char *dbError = (19 == (ErrorCode/0x10000L)) ? "Database " : "; /* Module No in high word */ ErrorCode &= 0xffffL; /* Error Code in low word */ printf("Exception Handler called with%s %sError: %d.\n", Fatal, dbError, ErrorCode); if(IsFatal) </pre>

```
exit(ErrorCode);
```

DBL_SetFilter()

Function	Assigns a filter to a specified field.
Category	Filter function.
Syntax	<pre>void DBL_SetFilter(DBL_HTABLE hTable, DBL_S32 FieldNo, DBL_U8* FilterStr, void* ValuePtr1, ...);</pre> <p>hTable: Handle to the table FieldNo: Number of the field for which a filter will be set FilterStr: Filter expression for the field, consisting of alphanumeric characters and one or more of the following operators: < > ? & =</p> <p>ValuePtr1..9: Replacement values for FilterStr. For example, if FilterStr contains the parameter %4, it is replaced by the fourth argument in this list. The list of replacement values must end with the parameter NULL.</p>
Remarks	<p>DBL_SetFilter assigns a filter to the field specified by FieldNo. Any filter that is already assigned to FieldNo for this table handle is removed before the new filter is attached. If FilterStr is empty or contains a NULL pointer, no filter will be assigned to FieldNo, and any filter that is currently assigned will be removed.</p> <p>For more information about filter syntax and relational operators, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_HREC hRec; DBL_S16 MaxValue; DBL_U8 FilterStr[100]; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hRec = DBL_AllocRec(hTable); /* Set filter on field 3 */ MaxValue = 500; DBL_SetFilter(hTable, 3, ">=200&<=%1", &MaxValue, NULL); /* Retrieve filter on field 3 */ DBL_GetFilter(hTable, 3, FilterStr, sizeof(FilterStr)); /* Variable FilterStr now contains the string ">=200&<=500" */ printf("Current filter on field 3 is %s\n", FilterStr); /* Scan records with a value in field 3 in the range 200-500 */ DBL-Allow(DBL_Err_RecordNotFound); if (DBL_FindRec(hTable, hRec, (DBL_U8*)"-")) do {</pre>

```

} while (DBL_NextRec(hTable, hRec, 1) != 0);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_SetLanguage()

Function Sets the language ID that will be used by the company that is currently open.

Category Database function

Syntax `void SetLanguage(System.Int32 LanguageID);`

LanguageID: the ID of the language to be used by the company.

Remarks

Example

```

DBL_S32 OrgLangId;
DBL_S32 NewLangId = 1031;
//(LangId for German)

OrgLangId = DBL_GetLanguage();

//Set new language
DBL_SetLanguage(NewLangId);

//Reset to original language
DBL_SetLanguage(OrgLangId);

```

DBL_SetMessageShowHandler()

Function Installs a customized message handler that will be used instead of the default message handler.

Category Error function

Syntax `void* DBL_SetMessageShowHandler(DBL_pFuncMessageShowHandler ShowFunc);`

ShowFunc: pointer to the function to use for showing messages.

Remarks DBL_SetMessageShowHandler installs a customized function for showing messages.

Example

```

void main(DBL_S16 argc, DBL_U8 *argv[], DBL_U8 *envp[])
{
/* ... */
DBL_SetMessageShowHandler(My_MessageShowHandler);
/* ... */
}

```

```

}

void DBL_CDECL My_MessageShowHandler(DBL_U8 *Msg, DBL_U32 MsgType, DBL_S32
ErrorCode)
{
DBL_S32 LnWidth = 70;
do {
DBL_U8 *Ret = (DBL_U8*)memchr(Msg, '\r', strlen((char*)Msg));

if (Ret > Msg+LnWidth) {
DBL_U8 *Space = (DBL_U8*)memchr_bckwrld(Msg, LnWidth, ' ');
if (Space)
Ret = Space;
}

if (Ret)
*Ret++ = 0;

printf("%s\n", Msg);
Msg = Ret;
} while(Msg && *Msg != 0);

fflush(stdout);
}

static void* memchr_bckwrld(const void *Dst, DBL_S32 Size, DBL_U8 Chr)
{
DBL_U8 *pS = (DBL_U8*)Dst+Size;
while(--pS >= Dst)
if (*pS == Chr)
return(pS);
return(NULL);
}

```

DBL_SetNavisionPath()

Function	Sets the path to the directory where Dynamics NAV is installed.
Category	Initialization function.
Syntax	<pre>void DBL_SetNavisionPath(DBL_U8 *Path);</pre> <p>Path: Path to the directory containing the Dynamics NAV files.</p>
Remarks	<p>Normally the C/Front library (cfront.dll) reads the registry in order to locate the Dynamics NAV DBMS system. However, if multiple Dynamics NAV systems are installed or if Dynamics NAV is not present on the system, the function DBL_SetNavisionPath should be called with the path to the directory of the Dynamics NAV installation or to a directory containing the following files from a Dynamics NAV installation:</p> <pre>dbm.dll nc_netb.dll nc_tcp.dll</pre>

slave.exe
fin.flf

DBL_SetNavisionPath must be called before any other function in the library, except DBL_Init, DBL_SetExceptionHandler and DBL_SetMessageShowHandler.

When you enter the path to Dynamics NAV, you must enter \\ for each \. For example, C:\\Program Files\\...

DBL_SetRange()

Function	Sets a range filter for a field.
Category	Filter function.
Syntax	<pre>void DBL_SetRange(DBL_HTABLE hTable, DBL_S32 FieldNo, const void* MinValue, const void* MaxValue);</pre> <p>hTable: Handle to the table FieldNo: Number of the field for which the filter is to be set MinValue: Starting value. If set to NULL, the filter is removed, regardless of the contents of MaxValue. MaxValue: Ending value. If NULL, the range is set to MinValue..MinValue.</p>
Remarks	<p>DBL_SetRange provides a quick way to set a simple filter on a field. Any filter already assigned to the field is removed.</p> <p>If MaxValue is set to NULL, the range is set to MinValue alone.</p> <p>Both MinValue and MaxValue must be of the same type as FieldNo.</p>
Example	<pre>DBL_HTABLE hTable; DBL_S16 MinValue; DBL_S16 MaxValue; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); /* Set range filter on field 3 */ /* Equals DBL_SetFilter(hTable, 3, ">=200&<=500") */ MinValue = 200; MaxValue = 500; DBL_SetRange(hTable, 3, &MinValue, &MaxValue); /* Retrieve range limits from current filter on field 3 */ DBL_GetRange(hTable, 3, &MinValue, &MaxValue); /* Retrieve range minimum limit from current filter on field 3 */ DBL_GetRange(hTable, 3, &MinValue, NULL); /* Retrieve range maximum limit from current filter on field 3 */ DBL_GetRange(hTable, 3, NULL, &MaxValue); /******/</pre>

```

/* Set one value filter on field 3          */
/* Equals DBL_SetFilter(hTable, 3, "=200") */
MinValue = 200;
DBL_SetRange(hTable, 3, &MinValue, NULL);

/* Retrieve range limits from current filter on field 3 */
DBL_GetRange(hTable, 3, &MinValue, &MaxValue);
printf("MinValue and MaxValue now both contain the value 200\n");

/******/

/* Remove filter on field 3          */
/* Equals DBL_SetFilter(hTable, 3, "") */
DBL_SetRange(hTable, 3, NULL, NULL);

/* Calling DBL_GetRange(hTable, 3, ..) now causes an exception */

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_SetView()

Function	Sets the current sort order, key and filters on a table.
Category	Table function
Syntax	<pre>void DBL_SetView(DBL_HTABLE hTable, DBL_U8 *ViewStr);</pre> <p>hTable: Handle to the table ViewStr: Pointer to the filter string</p>
Remarks	This function sets the sort order, key and filters on the current table. The string format is the same as the SourceTableView property on forms.
Example	<pre> DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); char ViewStr[250]; strncpy(ViewStr, "SORTING(No.)", sizeof(ViewStr)); DBL_SetView(hTable, (DBL_U8*)ViewStr); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_Str_Compare_Database()

Function	Compares two strings in a database to see which is the largest.
Category	Database function
Syntax	<pre>DBL_S32 DBL_Str_Compare_Database(const DBL_U8 *LeftStr, const DBL_U8 *RightStr);</pre> <p>LeftStr: the first string RightStr: the second string</p>
Remarks	<p>This function compares the Left and the Right string according to sort order and the difference between upper and lower case letters.</p> <p>Return values:</p>

Value	Meaning
1	Left > Right
0	Left == Right
-1	Left < Right

Example	<pre>DBL_S32 retVal; retVal = DBL_Str_Compare_Database("ABCDE", "ABCDE"); /* retVal = 0 */ retVal = DBL_Str_Compare_Database("ABCD", "ABCDE"); /* retVal = -1 */ retVal = DBL_Str_Compare_Database("ABCDE", "ABCD"); /* retVal = 1 */ retVal = DBL_Str_Compare_Database("ABCDe", "ABCDE"); /* retVal = -1 */ retVal = DBL_Str_Compare_Database("AAA", "ÃÃÃ"); /* retVal = -1 */ retVal = DBL_Str_Compare_Database("ABCDE", ""); /* retVal = 1 */</pre>
---------	--

DBL_Str_2_Alpha()

Function	Converts a string to an ALPHA variable.
Category	Conversion function.
Syntax	<pre>void DBL_Str_2_Alpha(DBL_U8* Alpha, DBL_S16 AlphaSize, DBL_U8* Str);</pre> <p>Alpha: Variable to receive the converted string AlphaSize: Size of Alpha, in bytes Str: String to be converted</p>
Remarks	<p>DBL_Str_2_Alpha converts a string to a variable of the ALPHA type and stores it in Alpha. If Alpha is not long enough to hold the converted string, the function raises an exception.</p> <p>For more information about ALPHA variables, see Appendix B.</p>

```

Example      DBL_U8 Alpha[12];
             DBL_U8 Str[11];

             DBL_Init();

             DBL_Str_2_Alpha(Alpha, sizeof(Alpha), "Number10");
             /* Variable Alpha now contains the alpha value "Number10" */

             DBL_Alpha_2_Str(Str, sizeof(Str), Alpha);
             /* Variable Str now contains the string value "Number10" */
             printf("Variable Str now contains the string value %s\n", Str);

             DBL_Exit();

```

DBL_Str_2_BCD()

Function Converts a string to a BCD (decimal number).

Category Conversion function.

Syntax `void DBL_Str_2_BCD(DBL_BCD* Bcd, DBL_U8* Str);`

Bcd: BCD variable in which the converted string is placed
Str: String to be converted

Remarks DBL_Str_2_BCD converts Str to a BCD variable and stores it in Bcd. Str must be in a format that prefixes negative numbers with a minus sign (-) and uses the period character as a decimal point (U.S.format). Leading and trailing blanks are ignored during conversion.

Value	String
1234	"1234"
-1234	"-1234"
1234.00	"1234"
1234.050	"1234.05"
11234.56	"1234.56"
.005	"0.005"

If Str does not contain a valid decimal number and cannot be converted, the function will raise an exception.

```

Example      DBL_BCD Bcd;
             DBL_U8 Str[11];

             DBL_Init();

             DBL_Str_2_BCD(&Bcd, "-1.2345");
             /* Variable Bcd now contains the value -1.2345 */

```



```

DBL_BCD_2_Str(Str, sizeof(Str), &Bcd);
/* Variable Str now contains the string value "-1.2345" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_BCD_2_Str(Str, 6+1, &Bcd);
/* Variable Str now contains the string value "*****" */
printf("Variable Str now contains the string value %s\n", Str);

DBL_Exit();

```

DBL_Str_2_Date()

Function	Converts a string to a DATE value.
Category	Conversion function
Syntax	<pre>void DBL_Str_2_Date(DBL_DATE *Date, DBL_U8 *Str);</pre> <p>Date: variable in which to place the converted value. Str: string containing the value to convert.</p>
Remarks	The Str string must conform to the format that has been set in the Regional Settings in the Control Panel. If the format is not correct, the function will raise an exception.
Example	<pre> DBL_U8 Str[50]; DBL_DATE cDate; /* ... */ /* Place date as string in Str. Note that the format depends */ /* upon the Regional Setting selected for the operating system */ sprintf(Str, "07-06-96"); /* Convert Str to DATE value */ DBL_Str_2_Date(&cDate, Str); /* ... */ </pre>

DBL_Str_2_DateFormula()

Function	Converts a string to a DateFormula value.
Category	Conversion function
Syntax	<pre>void DBL_Str_2_DateFormula(DBL_DATEFORMULA *DateFormula, DBL_U8 *Str);</pre> <p>DateFormula: variable in which to place the converted value. Str: string containing the value to convert.</p>
Remarks	This function converts a string to a dateformula.
Example	<pre>DBL_U8 Str[50];</pre>

```

DBL_DATEFORMULA cDateFormula;

/* ... */

/* Place dateformula as a string in Str. Note that the format depends */
/* upon the Regional Setting selected for the operating system */
sprintf(Str,"CM+1M"); /* current month plus one month*/
/* Convert Str to DATEFORMULA value */
DBL_Str_2_DateFormula(&cDateFormula,Str);

/* ... */

```

DBL_Str_2_Datetime()

Function	Converts a string to a Datetime value.
Category	Conversion function
Syntax	<pre>void DBL_Str_2_Datetime(DBL_DATETIME *Datetime, DBL_U8 *Str);</pre> <p>Datetime: variable in which to place the converted value. Str: string containing the value to convert.</p>
Remarks	The Str string must conform to the format that has been set in the Regional Settings in the Control Panel. If the format is not correct, the function will raise an exception.
Example	<pre> DBL_U8 Str[50]; DBL_DATETIME cDatetime; /* ... */ /* Place datetime as a string in Str. Note that the format depends */ /* upon the Regional Setting selected for the operating system */ sprintf(Str,"07-06-96 12:34:56"); /* Convert Str to DATETIME value */ DBL_Str_2_Datetime(&cDatetime,Str); /* ... */ </pre>

DBL_Str_2_Datetime_Ex()

Function	Converts a string to an extended Datetime value.
Category	Conversion function
Syntax	<pre>void Str_2_Datetime_Ex(DBL_Datetime *DatetimeDest,DBL_U8 *Str, DBL_BOOL UTC_Time);</pre> <p>DatetimeDest: variable in which to place the converted value. Str: string containing the value to convert. UTC_Time: whether or not to use UTC time.</p>

Remarks The Str string must conform to the format that has been set in the Regional Settings in the Control Panel. If the format is not correct, the function will raise an exception.

Example

```
DBL_U8 Str[50];
DBL_DATETIME cDatetime;

/* ... */

/* Place datetime as a string in Str. Note that the format depends */
/* upon the Regional Setting selected for the operating system */
sprintf(Str,"07-06-96 12:34:56");
/* Convert Str to DATETIME value */
DBL_Str_2_Datetime(&cDatetime,Str,true);

/* ... */
```

DBL_Str_2_Duration()

Function Converts a string to a DURATION.

Category Conversion function

Syntax void DBL_Str_2_Duration(DBL_DURATION *Duration, DBL_U8 *Str);

Duration: variable in which to place the converted value.
Str: string containing the value to convert.

Remarks This function converts a string and places the value in Duration.

Example

```
DBL_U8 Str[50];
DBL_DURATION cDuration;

/* ... */

/* Place duration as string in Str. */
sprintf(Str,"3600000"); /* one hour */
/* Convert Str to DURATION value */
DBL_Str_2_Duration(&cDuration,Str);

/* ... */
```

DBL_Str_2_Field()

Function Converts a string to a field

Category Conversion function

Syntax void DBL_Str_2_Field)(DBL_HTABLE hTable, DBL_HREC hRec, DBL_S32

FieldNo,DBL_U8 *Str);
hTable: Handle to the table
hRec: Handle to the record.

FieldNo: Number of the field in which the converted value will be placed.
 Str: String containing the value to convert.

Remarks This function converts/evaluates a string representation of a value into its normal representation and places it in the field in record handle identified by FieldNo. The field represented by FieldNo may be of any type.

Example

```

DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8 Str[11];

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);

DBL_FindRec(hTable, hRec, (DBL_U8*)"");

/* Let's assume that: */
/* Field 10 in hRec is a BCD type field */
/* Field 11 in hRec is a TEXT type field */

DBL_Str_2_Field(hTable, hRec, 10, "1.23456");
/* Field 10 now contains the 1.23456 as a BCD */
DBL_Str_2_Field(hTable, hRec, 11, "This is a test");
/* Field 11 now contains the text "This is a test" */

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_Str_2_Time()

Function Converts a string to a TIME value.

Category Conversion function

Syntax

```
void DBL_Str_2_Time(DBL_TIME *Time, DBL_U8 *Str);
```

Time: variable in which to place the converted value
 Str: string containing the value to convert

Remarks The Str string must conform to the format that has been set in the Regional Settings in the Control Panel. If the format is not correct, the function will raise an exception.

Example

```

DBL_U8 Str[50];
DBL_TIME cTime;

```

```

/* ... */

/* Place time as string in Str. Note that the format depends */
/* upon the Regional Setting selected for the operating system */
sprintf(Str,"17.05.57");
/* Convert Str to TIME value */
DBL_Str_2_Time(&cTime,Str);

/* ... */

```

DBL_Str_2_S64()

Function	Converts a string to a biginteger.
Category	Conversion function
Syntax	<pre>void Str_2_S64(DBL_S64 *S64Dest, DBL_U8 *Str);</pre> <p>S64Dest: The variable in which to place the converted value. Str: The string to be converted.</p>
Remarks	This function converts the string to a BigInteger and places the result in S64Dest.
Example	<pre>DBL_S64 bl; DBL_U8 Str[50]; DBL_Str_2_S64(&bl, "12345"); DBL_S64_2_Str(Str, sizeof(Str), &bl); printf("The value of the biginteger is %s", Str);</pre>

DBL_TableCaption()

Function	Returns the caption for a specific table.
Category	Table function
Syntax	<pre>DBL_U8* DBL_TableCaption(DBL_HTABLE hTable);</pre> <p>hTable: Handle to the table</p>
Remarks	<p>This function returns the multilanguage caption of the table to which the handle hTable is bound. The handle was created and bound to the table when DBL_OpenTable was called.</p> <p>This function cannot be used to change the table caption. Table captions can only be changed in C/SIDE.</p> <p>For more information about tables, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company");</pre>

```

DBL_OpenTable(&hTable, 15);

printf("Table number 15 has caption %s\n", DBL_TableCaption(hTable));

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();

```

DBL_TableDup()

Function	Duplicates the handle to a table.
Category	Table function
Syntax	<pre> DBL_HTABLE DBL_TableDup(DBL_HTABLE hSrcTable); hSrcTable: Handle to the table that is to be copied </pre>
Remarks	This function duplicates the handle to the table. The new handle includes any filters, sorting and lists that were included in the original handle. It is only a copy of the handle and not of the table. Both handles refer to the same table.
Example	<pre> DBL_HTABLE hTable; DBL_HTABLE hTableDup; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); DBL_OpenTable(&hTable, 15); hTableDup = DBL_TableDup(hTable); DBL_CloseTable(hTableDup); DBL_CloseTable(hTable); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_TableIsSame()

Function	Compares two tables to see if they have the same table definition.
Category	Table function.
Syntax	<pre> DBL_BOOL DBL_TableIsSame(const DBL_HTABLE hTable1, const DBL_HTABLE hTable2); hTable1: Handle to the first table hTable2: Handle to the second table that you want to compare the first table with </pre>

Remarks DBL_TableIsSame compares two tables to see if they have the same table definition. If they have the same table definition, DBL_TableIsSame returns TRUE. If they do not have the same table definition, DBL_TableIsSame returns FALSE.

DBL_TableName()

Function Retrieves the name of an open table.

Category Table function.

Syntax `DBL_U8* DBL_TableName(DBL_HTABLE hTable);`
 hTable: Handle to a table

Remarks DBL_TableName returns the name of the table to which handle hTable is bound. The handle was created and bound to the table when DBL_OpenTable was called.

This function cannot be used to change the table name. Table names can only be changed in C/SIDE.

For more information about tables, see the *Application Designer's Guide*.

Example

```
DBL_HTABLE hTable;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);

printf("Table number 15 is named %s\n", DBL_TableName(hTable));

DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();
```

DBL_TestSysPermission()

Function Tests whether or not the user has permission to execute a specific object.

Category Database function

Syntax `DBL_BOOL DBL_TestSysPermission(DBL_S32 ObjectNo);`
 ObjectNo: The number of the object that is to be tested.

Remarks DBL_TestSysPermission returns TRUE if the license file that the user is currently running has execute permission for the specified object and FALSE if it does not.

DBL_TableNo()

Function	Retrieves the number of the table with a specified table name.
Category	Table function.
Syntax	<pre>DBL_S32 DBL_TableNo(DBL_U8* TableName);</pre> <p>TableName: Table name</p>
Remarks	<p>This function is only needed by applications that do not support a table number. It is used to convert a name into a number for use by the DBL_Open Table function.</p> <p>If TableName does not exist, 0 is returned.</p> <p>For more information about tables, see the <i>Application Designer's Guide</i>.</p>
Example	<pre>DBL_S32 TableNo; DBL_HTABLE hTable; DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); DBL_OpenCompany("Test Company"); /* Look up the number of TestTable */ TableNo = DBL_TableNo("TestTable"); if (TableNo != 0) { DBL_OpenTable(&hTable, TableNo); /* ... */ DBL_CloseTable(hTable); } else printf("Table does not exist\n"); DBL_CloseCompany(); DBL_CloseDatabase(); DBL_Exit();</pre>

DBL_Time_2_HMST()

Function	Converts a TIME variable to hours, minutes, seconds, and thousandths of a second.
Category	Conversion function.
Syntax	<pre>void DBL_Time_2_HMST(DBL_S32* h, DBL_S32* m, DBL_S32* s, DBL_S32* t, DBL_TIME Time);</pre> <p>h: Variable to receive the value for hours m: Variable to receive the value for minutes s: Variable to receive the value for seconds</p>

t: Variable to receive the value for thousandths of a second
 Time: TIME variable to be converted

Remarks DBL_Time_2_HMST dismantles a TIME variable and creates values for hours, minutes, seconds and thousandths of a second. Any of the four output variables (h, m, s and t) can be set to NULL, if they are not needed.

If this function is called with Time=zero (undefined), an exception is raised. To prevent an exception being raised, test the value of the Time variable before you call this function.

Example

```
DBL_TIME Time;
DBL_S32 h,m,s,t;

DBL_Init();

DBL_HMST_2_Time(&Time, 14, 23, 30, 1);
/* Variable Time now contains the time 14:23:30.1 */

DBL_Time_2_HMST(&h, &m, &s, &t, Time);
/* Variables h,m,s and t now contain 14, 23, 30 and 1 */
printf("h,m,s and t now contain values %d, %d, %d and %d\n",
h,m,s,t);

DBL_Exit();
```

DBL_Time_2_Str()

Function Converts a TIME value to a string.

Category Conversion function.

Syntax

```
void DBL_Time_2_Str(DBL_U8 *Str, DBL_S16 StrSize, DBL_TIME Time);
```

Str: string in which to place the converted value
 StrSize: size (in bytes) of Str
 Time: variable containing the TIME value to convert

Remarks DBL_Time_2_Str converts the TIME value in Time to a string. StrSize is the size of the destination string: the number of bytes to place in Str. It is your responsibility to ensure that the converted value is not truncated.

Example

```
DBL_HTABLE hTable;
DBL_HREC hRec;
DBL_U8 resStr[50];
DBL_TIME *pTime;

DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);
DBL_OpenCompany("Test Company");
DBL_OpenTable(&hTable, 15);
hRec = DBL_AllocRec(hTable);
```

```

/* Retrieve a record: */
DBL_FindRec(hTable,hSrcRec,(DBL_U8*)"-" )
/* Get pTime from field 30: */
pTime = (DBL_TIME*)DBL_GetFieldDataAddr(hTable,hRec,30);
/* Convert pTime to a string: */
DBL_Time_2_Str(resStr,sizeof(resStr),*pTime);
/* Print out the string: */
printf("Time as string: %s\n", resStr);

DBL_FreeRec(hRec);
DBL_CloseTable(hTable);
DBL_CloseCompany();
DBL_CloseDatabase();
DBL_Exit();

```

DBL_UseCodeUnitsPermissions()

Function	Allows you to use the permissions of a specific codeunit.
Category	Security Function.
Syntax	<pre>void DBL_UseCodeUnitsPermissions(DBL_S32 CodeUnitID);</pre> <p>CodeUnitID: the ID of the codeunit whose permissions you want to use.</p>
Remarks	In order to run this function your permissions in this database must include execute permission for the codeunit whose permissions you want to use. The code unit you point to must have the property CFRONTMayUsePermissions set to Yes.
Example	<pre> DBL_Init(); DBL_OpenDatabase("test.fdb", 2000, 0); /* use the permissions for codeunit 55000 */ DBL_UseCodeUnitsPermissions(55000); /* ... */ DBL_CloseDatabase(); DBL_Exit(); </pre>

DBL_UserCount()

Function	Counts the user IDs in the database.
Category	Database function.
Syntax	DBL_S32 DBL_UserCount(void);

Remarks DBL_UserCount returns the number of users that are permitted to access the database tables. Users are created and assigned user IDs in C/SIDE.

This function is used to determine whether the function DBL_Login is needed. If at least one user is registered, all users are required to log in. The value returned by this function does not reflect how many users are currently connected.

Example

```
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);

/* Test whether login is required */
if (DBL_UserCount() > 0)
{
/* Log into database */
DBL_Login("MyUserID", "MyPassWord");

printf("Current userid is %s\n", DBL_UserID());
}

/* ... */

DBL_CloseDatabase();
DBL_Exit();
```

DBL_UserID()

Function Retrieves the login name of the current user.

Category Database function.

Syntax DBL_U8* DBL_UserID(void);

Remarks DBL_UserID returns the User ID that was used to connect to the current database from CFRONT and accepted by DBL_Login. The returned value is a pointer to a string containing the current User ID. If no DBL_Login has been issued, the function returns a pointer to an empty string.

User IDs can only be created, modified and deleted within C/SIDE.

Example

```
DBL_Init();
DBL_OpenDatabase("test.fdb", 2000, 0);

/* Test whether login is required */
if (DBL_UserCount() > 0)
{
/* Log into database */
DBL_Login("MyUserID", "MyPassWord");

printf("Current userid is %s\n", DBL_UserID());
}

/* ... */

DBL_CloseDatabase();
```

```
DBL_Exit();
```

DBL_YMD_2_Date()

Function	Converts year, month, day to a DATE variable.
Category	Conversion function.
Syntax	<pre>void DBL_YMD_2_DATE(DBL_DATE* Date, DBL_S32 y, DBL_S32 m, DBL_S32 d, DBL_BOOL Closing);</pre> <p>Date: DATE variable into which the converted date will be placed y: Value for a year in the range 0001..9999 m: Value for a month in the range 1..12 d: Value for a day in the range 1..31 Closing: 1 if Date is designated a closing date, otherwise 0</p>
Remarks	DBL_YMD_2_Date constructs a DATE variable.
Example	<pre>DBL_DATE Date; DBL_S32 y,m,d; DBL_BOOL c; DBL_Init(); DBL_YMD_2_Date(&Date, 2000, 5, 17, 0); /* Variable Date now contains the date May 17, 2000 */ DBL_Date_2_YMD(&y, &m, &d, &c, Date); /* Variables y,m,d and c now contain 2000, 5, 17 and 0 */ printf("y,m,d and c now contain %d, %d, %d and %d\n", y,m,d,c); DBL_Exit();</pre>

DBL_YMDHMST_2_Datetime()

Function	Converts year, month, day, hour, minute, second and thousandths of a second to a DATETIME variable.
Category	Conversion function.
Syntax	<pre>void DBL_YMDHMST_2_DATETIME(DBL_DATETIME* Datetime, DBL_s32 y, DBL_s32 m, DBL_s32 d, DBL_s32 h, DBL_s32 m, DBL_s32 s, DBL_s32 t);</pre> <p>Datetime: DATETIME variable that will receive the converted value y: Value for the year m: Value for the month d: Value for the day h: Value for the hours m: Value for the minutes</p>

```
s: Value for the seconds
t: Value for the thousandths of a second
```

Remarks The datetime must conform to the format that has been set in the Regional Settings in the Control Panel. If the format is not correct, the function will raise an exception.

Example

```
DBL_Init();

DBL_YMDHMST_2_Datetime(&Datetime, 2005, 5, 17, 14, 30, 45, 1);
/* Variable Datetime now contains the datetime May 17, 2005, 14:30:45.1 */

DBL_Datetime_2_YMDHMST(&y, &m, &d, &h, &m, &s, &t, Datetime);
/* Variables y,m,d,h,m,s and t now contain 2005, 5, 17, 14, 30, 45 and 1 */
printf("y,m,d,h,m,s and t now contain %d, %d, %d, %d, %d, %d and
%d\n",y,m,d,h,m,s,t);

DBL_Exit();
```

DBL_YMDHMST_2_Datetime_Ex()

Function Converts year, month, day, hour, minute, second and thousandths of a second to an extended DATETIME variable.

Category Conversion function.

Syntax

```
void DBL_YMDHMST_2_Datetime_Ex( DBL_Datetime Datetime, DBL_S32 y, DBL_S32 m,
DBL_S32 d, DBL_S32 h, DBL_S32 m, DBL_S32 s, DBL_S32 t, DBL_BOOL UTC_Time);
```

```
Datetime: DATETIME variable that will receive the converted value
y: Value for the year
m: Value for the month
d: Value for the day
h: Value for the hours
m: Value for the minutes
s: Value for the seconds
t: Value for the thousandths of a second
UTC_Time: whether or not the value is in UTC time
```

Remarks This function converts year, month, day, hour, minute, second and thousandths of a second to an DATETIME variable and allows you to specify whether it should be displayed in UTC time or according to the local settings on the computer.

Example

```
DBL_Init();

DBL_YMDHMST_2_Datetime(&Datetime, 2005, 5, 17, 14, 30, 45, 1, TRUE);
/* Variable Datetime now contains the datetime May 17, 2005, 14:30:45.1 */

DBL_Datetime_2_YMDHMST(&y, &m, &d, &h, &m, &s, &t, Datetime);
/* Variables y,m,d,h,m,s and t now contain 2005, 5, 17, 14, 30, 45 and 1 */
printf("y,m,d,h,m,s and t now contain %d, %d, %d, %d, %d, %d and
%d\n",y,m,d,h,m,s,t);

DBL_Exit();
```


Appendix A

C/Front Library Specifications

This appendix contains the specifications for the C/Front library functions.

- C/Front Library Specifications

A.1 C/Front Library Specifications

The following sections describe the specifications of the C/Front library functions.

Type and Constant Definitions

The library offers an expanded variety of alphanumeric, numeric, boolean and string types, known collectively as the DBL_ types.

typedef unsigned char	DBL_U8;
typedef unsigned short int	DBL_U16;
typedef signed long int	DBL_S16;
typedef unsigned long int	DBL_U32;
typedef signed long int	DBL_S32;
typedef DBL_U32	DBL_BOOL;
typedef DBL_U32	DBL_DATE;
typedef DBL_U32	DBL_TIME;
typedef DBL_O32	DBL_O32
typedef DBL_TABLE*	DBL_HTABLE;
typedef struct { DBL_U8 Exp; DBL_U8 Mant[9]; DBL_U8 Slack[2] }	DBL_BCD;
typedef double	DBL_DOUBLE
typedef biginteger { DBL_U32 LowPart; DBL_S32 HighPart }	DBL_S64
typedef DBL_S64	DBL_Duration
typedef DBL_S64	DBL_Datetime
typedef struct { DBL_U32 Data1; DBL_U16 Data2; DBL_U16 Data3; DBL_U8 Data4[8] }	DBL_GUID

Field Types

Data fields in a record can use any of the following nine field types. The right hand column shows the sizes of the different field types:

#define DBL_Type_O32	/* 4 bytes */
#define DBL_Type_BOOL	/* 4 bytes */
#define DBL_Type_BCD	/* 12 bytes */
#define DBL_Type_STR	/* Max Field Len + 1 byte */
#define DBL_Type_DATE	/* 4 bytes */
#define DBL_Type_TIME	/* 4 bytes */
#define DBL_Type_ALPHA	/* Max Field Len + 2 bytes */
#define DBL_Type_S32	/* 4 bytes */
#define DBL_Type_BLOB	/* Max 2 GB*/
#define DBL_Type_S64	/* 8 bytes */

#define DBL_Type_Duration	/* 8 bytes */
#define DBL_Type_Datetime	/* 2 x 4 bytes */
#define DBL_Type_GUID	/* 16 bytes (4+2+2+8) */

New field types cannot be defined. The type of a field can be retrieved with the function `DBL_FieldType`.

Declaration of Variables

Record field variables are declared as shown in the following table. The right hand column shows how the variable is supposed to be represented in the database.

```
#define My_Max_Len 10
/* Note that it is the length of the specific field */
/* in the database. *
```

DBL_O32	Option;	/* DBL_Type_O32 */
DBL_BOOL	Boolean;	/* DBL_Type_BOOL */
DBL_BCD	Decimal;	/* DBL_Type_BCD */
DBL_U8	Text[My_Max_Len+1];	/* DBL_Type_STR */
DBL_Date	Date;	/* DBL_Type_DATE */
DBL_Time	Time;	/* DBL_Type_TIME */
DBL_U8	Code[My_Max_Len+2];	/* DBL_Type_ALPHA */
DBL_S32	Integer;	/* DBL_Type_S32 */
DBL_BLOB	BLOB;	/* DBL_Type_BLOB */
DBL_S64	BigInteger	/* DBL_Type_S64 */
DBL_Duration	Duration	/* DBL_Type_DUR */
DBL_Datetime	DateTime	/* DBL_Type_DATETIME */
DBL_GUID	GUID	/* DBL_Type_GUID */

The names of the variables describe how the corresponding field types are represented in the C/SIDE Table Designer.

Field Classes

Data fields in a record belong to one of the following three classes:

#define DBL_Class_Normal	0
#define DBL_Class_FlowField	1
#define DBL_Class_FlowFilter	2

The class of a field can be retrieved with the function `DBL_FieldClass`.

Other C-Library Constant Definitions

See the `cf.h` file for definitions of all the constants.

Appendix B

The Alpha Type

This appendix contains a description of the Alpha data type
– an extended C string type.

B.1 Alpha Type

An Alpha type is an extended C string (zero-terminated string). The contents of the first byte differ, depending upon the contents of the string:

If the string contains only the numeric characters '0'..'9', the first byte contains the length of the string.

If the string contains non-numeric characters, the first byte contains the hex value FF.

This extra byte is used to give the correct weight to the strings when comparing two alpha type fields.

Ordinary strings

```
char a[] = "990";  
char b[] = "1000";
```

When compared, a is greater than b, and is sorted as follows:

```
"1000"  
"990"
```

Alpha strings

```
char a[] = "\3"990"; /* \3 is the length of 990 */  
char b[] = "\4"1000"; /* \4 is the length of 1000 */
```

When compared, a is less than b, and is sorted as follows:

```
"\3"990"  
"\4"1000"
```